

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

Glass Cleaner

Product no.

-

REACH registration number

Not applicable

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

NA

Washing and Cleaning Products (including solvent based products) (PC35)

Non industrial spraying (PROC 11)

Formulation [mixing] of preparations and/or re-packaging (excluding alloys) (SU 10)

Professional uses: Public domain (administration, education, entertainment, services, craftsmen) (SU 22)

Formulation of preparations (ERC2)

Stone, plaster, cement, glass and ceramic articles (AC4)

Uses advised against

-

The full text of any mentioned and identified use categories are given in section 16

1.3. Details of the supplier of the safety data sheet

Company and address

Pureno A/S

Rønnevangs Allé 8

3400 Hillerød

Denmark

Tlf.: +45 70 260 267

Contact person

Kenneth Christensen

E-mail

mail@pureno.dk

SDS date

2017-01-02

SDS Version

2.0

1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service). See section 4 "First aid measures".

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Aerosol 3; H229

Eye Irrit. 2; H319

See full text of H-phrases in section 2.2.

2.2. Label elements

▼ Hazard pictogram(s)

Signal word

Warning

Hazard statement(s)

Pressurised container: May burst if heated. (H229)

Causes serious eye irritation. (H319)

▼ Safety statement(s)**General**If medical advice is needed, have product container or label at hand. (P101).
Keep out of reach of children. (P102).**Prevention**

Do not pierce or burn, even after use. (P251).

Response

Wear eye protection. (P280).

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. (P305+P351+P338).

Storage

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F. (P410+P412).

Disposal

-

Identity of the substances primarily responsible for the major health hazards

-

▼ 2.3. Other hazards

This product contains an organic solvent. Repeated or prolonged exposure to organic solvents may result in adverse effects to the nervous system and internal organs such as liver and kidneys.

Additional labelling

28 mass percent of the content is flammable

Additional warnings

-

VOC

-

SECTION 3: Composition/information on ingredients**▼ 3.1/3.2. Substances/Mixtures**

NAME: ethanol
 IDENTIFICATION NOS.: CAS-no: 64-17-5 EC-no: 200-578-6 Index-no: 603-002-00-5
 CONTENT: 15-25%
 CLP CLASSIFICATION: Flam. Liq. 2, Eye Irrit. 2
 H225, H319
 NOTE: S

NAME: propan-2-ol
 IDENTIFICATION NOS.: CAS-no: 67-63-0 EC-no: 200-661-7 Index-no: 603-117-00-0
 CONTENT: 10-15%
 CLP CLASSIFICATION: Flam. Liq. 2, Eye Irrit. 2, STOT SE 3
 H225, H319, H336
 NOTE: S

NAME: carbon dioxide
 IDENTIFICATION NOS.: CAS-no: 124-38-9 EC-no: 204-696-9
 CONTENT: 5-10%
 CLP CLASSIFICATION: Refrig. Liq. Gas
 H281
 NOTE: L

NAME: 2,2',2''-nitrilotriethanol
 IDENTIFICATION NOS.: CAS-no: 102-71-6 EC-no: 203-049-8
 CONTENT: 1-3%
 CLP CLASSIFICATION: Skin Irrit. 2, Eye Irrit. 2
 H315, H319

(*) See full text of H-phrases in chapter 16. Occupational exposure limits are listed in section 8, if these are available.

S = Organic solvent L = European occupational exposure limit.

Other information

Eye Cat. 2 Sum = Sum(Ci/S(G)CLi) = 2,4064 - 3,6096

Skin Cat. 2 Sum = Sum(Ci/S(G)CLi) = 0,1184 - 0,1776

SECTION 4: First aid measures**4.1. Description of first aid measures****▼ General information**

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. The doctor can contact The National Poisons Information Service (dial 111, 24 h service). Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

▼ Inhalation

Bring the person into fresh air and stay with him.

▼ Skin contact

Immediately remove contaminated clothing and shoes. Ensure that skin, which has been exposed to the material, is washed thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.

▼ Eye contact

Remove contact lenses and open eyes widely. Flush eyes with water or saline water(20-30°C) for at least 15 minutes. Seek medical assistance and continue flushing during transport.

▼ Ingestion

Provide plenty of water for the person to drink and stay with him/her. In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the victim lean forward with head down to avoid inhalation of- or choking on vomited material.

Burns

Not applicable

▼ 4.2. Most important symptoms and effects, both acute and delayed

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

▼ 4.3. Indication of any immediate medical attention and special treatment needed

No special

Information to medics

Bring this safety data sheet.

SECTION 5: Firefighting measures**▼ 5.1. Extinguishing media**

Recommended: alcohol-resistant foam, carbonic acid, powder, water mist. Waterjets should not be used, since they can spread the fire.

▼ 5.2. Special hazards arising from the substance or mixture

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous catabolic substances are produced. These are: Carbon oxides. Fire will result in dense black smoke. Exposure to combustion products may harm your health. Fire fighters should wear appropriate protection equipment. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

▼ 5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

No specific requirements.

6.2. Environmental precautions

No specific requirements.

▼ 6.3. Methods and material for containment and cleaning up

Use sand, sawdust, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations. To the extent possible cleaning is performed with normal cleaning agents. Avoid use of solvents.

▼ 6.4. Reference to other sections

See section on "Disposal considerations" in regard of handling of waste. See section on 'Exposure controls/personal protection' for protective measures.

SECTION 7: Handling and storage

▼ 7.1. Precautions for safe handling

Avoid static electricity. Protect electrical equipment in accordance with current standards. To divert static electricity during transmission, containers must be grounded and connected by wire with the receiving containers. Do not use spark-forming tools.

Smoking, storage of tobacco, consumption and storage of food or liquids are not allowed in the workrooms. See section on 'Exposure controls/personal protection' for information on personal protection.

▼ 7.2. Conditions for safe storage, including any incompatibilities

Always store in containers of the same material as the original container. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Beware, this chemical can form peroxides. The potential contents of peroxide must be controlled regularly after opening, for example every 6th month.

Storage temperature

No data available.

▼ 7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

▼ OEL

carbon dioxide (EH40/2005)

Long-term exposure limit (8-hour TWA reference period): 5000 ppm | 9150 mg/m³

Short-term exposure limit (15-minute reference period): 15000 ppm | 27400 mg/m³

ethanol (EH40/2005)

Long-term exposure limit (8-hour TWA reference period): 1000 ppm | 1920 mg/m³

Short-term exposure limit (15-minute reference period): - ppm | - mg/m³

▼ DNEL / PNEC

DNEL (ethanol): 950 mg/m³

Exposure: Inhalation

Duration of Exposure: Long term – Systemic effects - Workers

DNEL (ethanol): 1900 mg/m³

Exposure: Inhalation

Duration of Exposure: Short term – Local effects - Workers

DNEL (ethanol): 343 mg/kg legemsvægt pr. dag

Exposure: Dermal

Duration of Exposure: Long term – Systemic effects - Workers

DNEL (ethanol): 114 mg/m³

Exposure: Inhalation

Duration of Exposure: Long term – Systemic effects - General population

DNEL (ethanol): 950 mg/m³

Exposure: Inhalation

Duration of Exposure: Short term – Local effects - General population

DNEL (ethanol): 206 mg/kg legemsvægt pr. dag

Exposure: Dermal

Duration of Exposure: Long term – Systemic effects - General population

DNEL (ethanol): 87 mg/kg legemsvægt pr. dag

Exposure: Oral

Duration of Exposure: Long term – Systemic effects - General population

DNEL (propan-2-ol): 888 mg/kg bw/dag

Exposure: Dermal

Duration of Exposure: Long term – Systemic effects - Workers

DNEL (propan-2-ol): 500 mg/m³

Exposure: Inhalation

Duration of Exposure: Long term – Systemic effects - Workers

DNEL (propan-2-ol): 319mg/kg bw/dag

Exposure: Dermal

Duration of Exposure: Long term – Systemic effects - General population

DNEL (propan-2-ol): 89mg/m³

Exposure: Inhalation
 Duration of Exposure: Long term – Systemic effects - General population
 DNEL (propan-2-ol): 26mg/kg bw/dag
 Exposure: Oral
 Duration of Exposure: Long term – Systemic effects - General population

PNEC (ethanol): 0,96 mg/l
 Exposure: Freshwater
 PNEC (ethanol): 0,79 mg/l
 Exposure: Marine water
 PNEC (ethanol): 2,75 mg/l
 Exposure: Intermittent release
 PNEC (ethanol): 580 mg/l
 Exposure: Sewage Treatment Plant
 PNEC (ethanol): 3,6 mg/kg
 Exposure: Freshwater sediment
 PNEC (ethanol): 2,9 mg/kg
 Exposure: Marine water sediment
 PNEC (ethanol): 0,63 mg/kg
 Exposure: Soil
 PNEC (propan-2-ol): 552mg/kg
 Exposure: Marine water sediment
 PNEC (propan-2-ol): 140,9 mg/l
 Exposure: Freshwater
 PNEC (propan-2-ol): 28 mg/kg
 Exposure: Soil
 PNEC (propan-2-ol): 140,9 mg/l
 Exposure: Marine water
 PNEC (propan-2-ol): 140,9 mg/l
 Exposure: Intermittent release
 PNEC (propan-2-ol): 251 mg/l
 Exposure: Sewage Treatment Plant
 PNEC (propan-2-ol): 552 mg/kg
 Exposure: Freshwater sediment

8.2. Exposure controls

- ▼ Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

- ▼ Observe general occupational hygiene standards.

Exposure scenarios

In the event exposure scenarios are appended to the safety data sheet, the operational conditions and risk management measures in these shall be complied with.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

Airborne gas and dust concentrations must be kept at a minimum and below current limit values (see above). Installation of an exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure emergency eyewash and -showers are clearly marked.

Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

Measures to avoid environmental exposure

No specific requirements.

Individual protection measures, such as personal protective equipment



Generally

Use only CE marked protective equipment.

Respiratory Equipment

If ventilation at the work place is insufficient, use a half- or whole mask with an appropriate filter or an air-supplied breathing apparatus depending on the concrete work situation and how long you will be using the product.

Skin protection

Wear appropriate protection clothing, e.g. coveralls in polypropylene approved type 6 and Category III.

Hand protection

Recommended: Nitrile rubber

▼ **Eye protection**

Wear safety glasses with side shields.

SECTION 9: Physical and chemical properties

▼ **9.1. Information on basic physical and chemical properties**

Form	Aerosol
Colour	Clear
Odour	Alcohol odor
pH	No data available.
Viscosity (40°C)	No data available.
Density (g/cm ³)	0,9

▼ **Phase changes**

Melting point (°C)	No data available.
Boiling point (°C)	No data available.
Vapour pressure	No data available.

▼ **Data on fire and explosion hazards**

Flashpoint (°C)	35
Ignition (°C)	No data available.
Self-ignition (°C)	No data available.
Explosion limits (Vol %)	No data available.

▼ **Solubility**

Solubility in water	Soluble
n-octanol/water coefficient	No data available.

▼ **9.2. Other information**

Solubility in fat (g/L)	No data available.
-------------------------	--------------------

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available

▼ **10.2. Chemical stability**

The product is stable under the conditions, noted in the section "Handling and storage".

10.3. Possibility of hazardous reactions

No special

10.4. Conditions to avoid

No special

▼ **10.5. Incompatible materials**

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Substance	Species	Test	Route of exposure	Result
2,2',2''-nitrilotriethanol	Rabbit	LD50	Oral	2200 mg/kg
2,2',2''-nitrilotriethanol	Mouse	LD50	Oral	5846 mg/kg
2,2',2''-nitrilotriethanol	Guinea pig	LD50	Oral	2200 mg/kg
carbon dioxide	Rat	LC50	Inhalation	470000 ppm 0,5 h
propan-2-ol	Rabbit	LD50	Dermal	>2000 mg/kg
propan-2-ol	Rat	LD50	Oral	5840 mg/kg
propan-2-ol	Rat	LC50	Inhalation	47,5mg/l 8 h
propan-2-ol	Rat	LC50	Inhalation	66,1mg/l 4 h
ethanol	Rabbit	LD50	Dermal	>17100 mg/kg
ethanol	Rat	LD50	Oral	10470 mg/kg
ethanol	Rat	LC50	Inhalation	124,7 mg/l

▼ **Skin corrosion/irritation**

No data available.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

No data available.

Germ cell mutagenicity

No data available.

Carcinogenicity

No data available.

Reproductive toxicity

No data available.

STOT-single exposure

No data available.

STOT-repeated exposure

No data available.

Aspiration hazard

No data available.

▼ Long term effects

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

SECTION 12: Ecological information

12.1. Toxicity

Substance	Species	Test	Duration	Result
2,2',2"-nitrilotriethanol	Fish	LC50		1800-11800 mg/l
2,2',2"-nitrilotriethanol	Daphnia	LC50		1390-2038 mg/l
2,2',2"-nitrilotriethanol	Algae	EC50		470-750 mg/l
2,2',2"-nitrilotriethanol	Crustacean	IC50		>5000 mg/l
propan-2-ol	Algae	NOEC	8d	>1800 mg/l
propan-2-ol	Fish	LC50	96 h	8970-9280 mg/l
propan-2-ol	Daphnia	EC50	24 h	9714 mg/l
propan-2-ol	Crustacean	EC10	18 h	5175 mg/l
propan-2-ol	Crustacean	EC50		>1000mg/l
ethanol	Fish	LC50	48 h	8150 mg/l
ethanol	Fish	LC50	96h	1100 mg/l
ethanol	Daphnia	EC50	48 h	9268-14221 mg/l
ethanol	Algae	EC0	168 h	5000 mg/l
ethanol	Crustacean	EC0	16 h	6500 mg/l

12.2. Persistence and degradability

Substance	Biodegradability	Test	Result
2,2',2"-nitrilotriethanol	Yes	No data available	No data available
propan-2-ol	Yes	Modified OECD Screening Test	95%
ethanol	Yes	No data available	No data available

12.3. Bioaccumulative potential

Substance	Potential bioaccumulation	LogPow	BCF
carbon dioxide	No	0,83	No data available
propan-2-ol	No	No data available	No data available
ethanol	No	No data available	No data available

12.4. Mobility in soil

carbon dioxide: Log Koc= 0,735677, Calculated from LogPow (High mobility potential.).

12.5. Results of PBT and vPvB assessment

No data available

12.6. Other adverse effects

No special

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product is covered by the regulations on hazardous waste.

Waste

EWC code

16.05.04

Specific labelling

-

▼ Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

14.1 – 14.4

This product is within scope of the regulations of transport of dangerous goods.

▼ ADR/RID

14.1. UN number 1950

14.2. UN proper shipping name -

14.3. Transport hazard class(es) 2.2

14.4. Packing group -

Notes -

Tunnel restriction code -

IMDG

UN-no. 1950

Proper Shipping Name Aerosols

Class 2.2

PG* -

EmS F-D, S-U

MP** NO

Hazardous constituent -

▼ IATA/ICAO

UN-no. 1950

Proper Shipping Name Aerosols

Class 2.2

PG* -

14.5. Environmental hazards

-

14.6. Special precautions for user

-

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

No data available

(*) Packing group

(**) Marine pollutant

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

▼ Restrictions for application

People under the age of 18 shall not be exposed to this product cf. Council Directive 94/33/EC of 22 June 1994 on the protection of young people at work.

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

Demands for specific education

-

Additional information

-

Sources

Council Directive 94/33/EC of 22 June 1994 on the protection of young people at work.

Council Directive 75/324/EEC of 20 May 1975 on the approximation of the laws of the Member States relating to aerosol dispensers.

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677. The Stationery Office, 2002.

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (CLP). EC regulation 1907/2006 (REACH).

15.2. Chemical safety assessment

No

SECTION 16: Other information

▼ Full text of H-phrases as mentioned in section 3

H225 - Highly flammable liquid and vapour.

H281 - Contains refrigerated gas; may cause cryogenic burns or injury.

H315 - Causes skin irritation.

H319 - Causes serious eye irritation.

H336 - May cause drowsiness or dizziness.

The full text of identified uses as mentioned in section 1

PC35 = Washing and Cleaning Products (including solvent based products)

PROC 11 = Non industrial spraying

SU 10 = Formulation [mixing] of preparations and/or re-packaging (excluding alloys)

SU 22 = Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

ERC2 = Formulation of preparations

AC4 = Stone, plaster, cement, glass and ceramic articles

Other symbols mentioned in section 2



Other

In accordance with Regulation (EC) No. 1272/2008 (CLP) the evaluation of the classification of the mixture is based on:

The classification of the mixture in regard of physical hazards has been based on experimental data.

The classification of the mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The safety data sheet is validated by

KAO

Date of last essential change (First cipher in SDS version)

2016-02-17

Date of last minor change (Last cipher in SDS version)

2016-02-17