According to EC-Regulation 1907/2006 (REACH)

Pureno Care

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

Release agent Product no.

REACH registration number Not applicable

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

NA

Uses advised against

The full text of any mentioned and identified use categories are given in section 16

1.3. Details of the supplier of the safety data sheet

Company and address

Pureno A/S Rønnevangs Allé 8 3400 Hillerød Denmark Tlf.: +45 70 260 267

Contact person

Kenneth Christensen E-mail

mail@pureno.dk

SDS date

2016-01-20

SDS Version 2.0

1.4. Emergency telephone number

Use your national or local emergency number See section 4 "First aid measures"

SECTION 2: Hazards identification

▼2.1. Classification of the substance or mixture

Aerosol 1; H229 Aerosol 2; H223 STOT SE 3; H336

See full text of H-phrases in section 2.2. 2.2. Label elements





Hazard statement(s) Pressurised container: May burst if heated. (H229)

Pureno Care

Flammable aerosol. (H223) May cause drowsiness or dizziness. (H336)

▼Safety statement(s)	General	If medical advice is needed, have product container or label at hand. (P101). Keep out ofreach ofchildren. (P102).
	Prevention	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. (P210).
	Response	Call a POISON CENTER/doctor if you feel unwell. (P312).
	Storage	Protect from sunlight. Do no expose to temperatures exceeding 50 °C/122°F. (P410+P412).
	Disposal	Dispose of contents/container to an approved waste disposal plant. (P501).
Identity of t	he substances	primarily responsible for the major health hazards

Naphtha (petroleum), hydrotreated heavy (0,1<benzen)

2.3. Other hazards

Additional labelling

Additional warnings

VOC

SECTION 3: Composition/information on ingredients

▼3.1/3.2. Substances/Mixtures

NAME: IDENTIFICATION NOS.: CONTENT: CLP CLASSIFICATION:	Naphtha (petroleum), hydrotreated heavy (0,1 <benzen) CAS-no: 64742-48-9 EC-no: 265-150-3 Index-no: 649-327-00-6 60-80% Flam. Liq. 3, STOT SE 3, Asp. Tox. 1 H226, H304, H336, EUH066</benzen)
NAME: IDENTIFICATION NOS.: CONTENT: CLP CLASSIFICATION:	carbon dioxide CAS-no: 124-38-9 EC-no: 204-696-9 5-10% Refrig. Liq. Gas H281

(*) See full text of H-phrases in chapter 16. Occupational exposure limits are listed in section 8, if these are available.

Other informations

SECTION 4: First aid measures

4.1. Description of first aid measures

VGeneral information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor, if in doubt about the injured person's condition or if the symptoms continue. Never give an unconscious person water or similar.

Inhalation

Get the person into fresh air and stay with them.

Skin contact

Remove contaminated clothing and shoes at once. Skin that has come in contact with the material must be washed thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.

Eye contact

Remove contact lenses. Flush eyes immediately with plenty of water (20-30°C) for at least 15 minutes and continue until irritation stops. Make sure you flush under the upper and lower eyelids. If irritation continues, contact a doctor.

Ingestion

Give the person plenty to drink and stay with the person. If the person feels unwell, contact a doctor immediately and take this safety data sheet or the label from the product with you. Do not induce vomiting unless recommended by the doctor. Hold head facing down so that no vomit runs back into the mouth and throat.

Pureno Care

Burns

Rinse with water until the pain stops and continue for 30 minutes.

4.2. Most important symptoms and effects, both acute and delayed No special

4.3. Indication of any immediate medical attention and special treatment needed Call a POISON CENTER/doctor if you feel unwell.

Information to medics

Bring this safety data sheet.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Recommended: alcohol-resistant foam, carbonic acid, powder, water mist. Water jets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

If the product is exposed to high temperatures, as in the case of fire, dangerous catabolic substances are produced. These are: Carbon oxides. Fire will result in thick black smoke. Exposure to catabolic products can damage your health. Fire fighters should use proper protection gear. Closed containers, which are exposed to fire, should be cooled with water. Do not let fire-extinguishing water run into sewers and other water courses.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact.

SECTION 6: Accidental release measures

V 6.1. Personal precautions, protective equipment and emergency procedures

Avoid inhalation of vapours from waste material. Stores that have not ignited must be cooled by water mist. Where possible, remove flammable materials. Make sure there is sufficient ventilation.

6.2. Environmental precautions

No specific requirements.

• 6.3. Methods and material for containment and cleaning up

Use sand, sawdust, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations. Cleaning should be done as far as possible using normal cleaning agents. Solvents should be avoided.

6.4. Reference to other sections

See section on "Disposal" with regard to the handling of waste. See section on 'Exposure controls/personal protection' for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

See section on 'Exposure controls/personal protection' for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Always store in containers of the same material as the original. Must be stored in a cool and ventilated area, away from possible sources of combustion.

Storage temperature

No data available.

7.3. Specific end use(s)

This product should only be used for applications described in Section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

VOEL

carbon dioxide (EH40/2005) Long-term exposure limit (8-hour TWA reference period): 5000 ppm | 9150 mg/m3 Short-term exposure limit (15-minute reference period): 15000 ppm | 27400 mg/m3

DNEL / PNEC

Pureno Care

8.2. Exposure controls

Compliance with the stated exposure limits values should be checked on a regular basis. General recommendations

V Observe general occupational hygiene.

Exposure scenarios

If there is an appendix to this safety data sheet, the indicated exposure scenarios must be complied.

Trade users are covered by the rules of the working environment legislation on maximum concentrations for exposure. See work hygiene threshold values below.

Appropriate technical measures

Airborne gas and dust concentrations must be kept as low as possible and below the current threshold values (see below). Use for example an exhaust system if the normal air flow in the work room is not sufficient. Make sure that eyewash and emergency showers are clearly marked.

Hygiene measures

Whenever you take a break in using this product and when you have finished using it, all exposed areas of the body must be washed. Always wash hands, forearms and face.

Measures to avoid environmental exposure

No specific requirements.

Individual protection measures, such as personal protective equipment



Use only CE marked protective equipment. Respiratory Equipment No specific requirements. Skin protection Special work clothing should be used. Hand protection Recommended: Nitrile rubber. : NA Eye protection

No specific requirements.

SECTION 9: Physical and chemical properties

9.1. Information on ba	sic physical	and chemical properties			
Form	Colour	Odour	рΗ	Viscosity	Density (g/cm3)
Aerosol	Clear	Aromatic	-	-	-
Phase changes					
Melting point (°C)		Boiling point (°C)		Vapour pressure (mm Hg)	
-		-		-	
Data on fire and ex	plosion haza				
Flashpoint (°C)		Ignition (°C)		Self ignition (°C)	
42		-		-	
Explosion limits (Vol %)		Oxidizing properties			
-		-			
Solubility					
Solubility in water		n-octanol/water coefficient			
Insoluble		•			
9.2. Other information					
Solubility in fat		Additional information			
-		N/A			

SECTION 10: Stability and reactivity

- 10.1. Reactivity
 - No data available



10.2. Chemical stability

The product is stable under the conditions, noted in the section on "Handling and storage".

- 10.3. Possibility of hazardous reactions No special
- 10.4. Conditions to avoid
- Avoid static electricity.
- **V** 10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reductants agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity				
Substance	Species	Test	Route of exposure	Result
carbon dioxide	Rat	LC50	Inhalation	470000 ppm 0,5 h
Naphtha (petroleum), hydrotrea	Rat	LD50	Oral	>5000mg/kg
Naphtha (petroleum), hydrotrea	Rat	LC50	Inhalation	>5mg/L
Naphtha (petroleum), hydrotrea	Rat	LD50	Dermal	>5000mg/kg
Skin corrosion/irritation				
No data available.				
Serious eye damage/irritation				
No data available.				
Respiratory or skin sensitisation	on			
No data available.				
Germ cell mutagenicity				
No data available.				
Carcinogenicity				
No data available.				
Reproductive toxicity				
No data available.				
STOT-single exposure				
May cause drowsiness or dizz	ziness.			
STOT-repeated exposure				
No data available.				
Aspiration hazard				
No data available.				
Long term effects				

No special

SECTION 12: Ecological information

▼12.1. Toxicity Substance Naphtha (petroleum), hydrotrea Naphtha (petroleum), hydrotrea Naphtha (petroleum), hydrotrea	<mark>Species</mark> Daphnia Fish Algae	Test EC50 LC50 EC50	Test duration 48 h 96 h	Result 1000mg/L >1000 mg/l >1000mg/l
12.2. Persistence and degradabi	lity			
Substance Naphtha (petroleum), hydrotrea	Biodegradability Yes		Test No data available	Result No data available
▼ 12.3. Bioaccumulative potential				
Substance carbon dioxide	Potential bioaccumulation		LogPow 0,83	BFC No data available
 12.4. Mobility in soil carbon dioxide: Log Koc= 0,73 12.5. Results of PBT and vPvB ass No data available 12.6. Other adverse effects No special 		l from LogPow (Hi	gh mobility potential.).	

Pureno | Care

SECTION 13: Disposal considerations

13.1. Waste treatment methods

The product is covered by the regulations on dangerous waste.

Waste EWC code

16.05.04 Specific labelling

Contaminated packing

Packaging which contains leftovers from the product must be disposed of in the same way as the product.

SECTION 14: Transport information

1

This product is covered by the conventions on dangerous goods.

4. <u>1</u> – 14.4	
ADR/RID	
14.1. UN number	1950
14.2. UN proper shipping name	
14.3. Transport hazard class(es)	2.1
14.4. Packing group	-
Notes	-
Tunnel restriction code	-
VIMDG	
UN-no.	1950
Proper Shipping Name	Aerosoler
Class	2.1
PG*	1
EmS	F-D, S-U
MP**	NO
Hazardous constituent	-
UN-no.	
Proper Shipping Name	
Class	

PG*

14.5. Environmental hazards

```
14.6. Special precautions for user
```

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

- No data available
- (*) Packing group
- (**) Marine pollutant

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

Demands for specific education

Additional information

Sources



Council Directive 75/324/EEC of 20 May 1975 on the approximation of the laws of the Member States relating to aerosol dispensers. EC Regulation 1272/2008 (CLP). EC regulation 1907/2006 (REACH). **15.2. Chemical safety assessment**

No

SECTION 16: Other information

VFull text of H-phrases as mentioned in section 3

H226 - Flammable liquid and vapour.

H281 - Contains refrigerated gas; may cause cryogenic burns or injury.

H304 - May be fatal if swallowed and enters airways.

H336 - May cause drowsiness or dizziness.

EUH066 - Repeated exposure may cause skin dryness or cracking.

The full text of identified uses as mentioned in section 1

Other symbols mentioned in section 2



Other

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

A change (in proportion to the last essential change (first cipher in SDS version)) is marked with a blue triangle.

The safety data sheet is validated by KAO Date of last essential change (First cipher in SDS version) 2014-01-31 Date of last minor change (Last cipher in SDS version) 2014-01-31

> ALPHAOMEGA. Licens nr.:3009391743 www.chymeia.com