

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

NSF-H1 Universal Grease White

Product no.

NSF(151509) H1

REACH registration number

Not applicable

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

NA

Lubricants, Greases and Release Products (PC24)

Nonindustrial spraying (PROC 11)

Formulation [mixing] of preparations and/or re-packaging (excluding alloys) (SU 10)

Professional uses: Public domain (administration, education, entertainment, services, craftsmen) (SU 22)

Formulation of preparations (ERC2)

Metal articles (AC7)

Uses advised against

-

The full text of any mentioned and identified use categories are given in section 16

1.3. Details of the supplier of the safety data sheet

Company and address

Pureno A/S

Rønnevangs Allé 8

3400 Hillerød

Denmark

Tlf.: +45 70 260 267

Contact person

Kenneth Christensen

E-mail

mail@pureno.dk

SDS date

2018-03-20

SDS Version

2.0

1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service). See section 4 "First aid measures".

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Aerosol 1; H222, H229

See full text of H-phrases in section 2.2.

2.2. Label elements

▼ Hazard pictogram(s)**Signal word**

Danger

▼ Hazard statement(s)

Extremely flammable aerosol. (H222)
 Pressurised container: May burst if heated. (H229)

Safety statement(s)

General If medical advice is needed, have product container or label at hand. (P101).
 Keep out of reach of children. (P102).

Prevention Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
 No smoking. (P210).
 Do not spray on an open flame or other ignition source. (P211).
 Do not pierce or burn, even after use. (P251).

Response -

Storage Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.
 (P410+P412).

Disposal -

▼ Identity of the substances primarily responsible for the major health hazards

Not applicable

▼ 2.3. Other hazards

This product contains an organic solvent. Repeated or prolonged exposure to organic solvents may result in adverse effects to the nervous system and internal organs such as liver and kidneys.

▼ Additional labelling

Not applicable

▼ Additional warnings

Not applicable

VOC

Not applicable

SECTION 3: Composition/information on ingredients**▼ 3.1/3.2. Substances/Mixtures**

NAME:	dimethoxymethan
IDENTIFICATION NOS.:	CAS-no: 109-87-5 EC-no: 203-714-2
CONTENT:	40-60%
CLP CLASSIFICATION:	Flam. Liq. 2 H225
NOTE:	S

NAME:	carbon dioxide
IDENTIFICATION NOS.:	CAS-no: 124-38-9 EC-no: 204-696-9
CONTENT:	5 - <10%
CLP CLASSIFICATION:	Refrig. Liq. Gas H281
NOTE:	L

(* See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.
 S = Organic solvent L = European occupational exposure limit.

Other information

-

SECTION 4: First aid measures**4.1. Description of first aid measures****▼ General information**

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. The doctor can contact The National Poisons Information Service (dial 111, 24 h service).
 Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

▼ Inhalation

Bring the person into fresh air and stay with him/her.

▼ Skin contact

Immediately remove contaminated clothing and shoes. Ensure that skin, which has been exposed to the material, is washed thoroughly with soap and water. Skin cleanser can be used. DO NOT use solvents or

thinners.

▼ Eye contact

Remove contact lenses. Flush eyes immediately with plenty of water or isotonic water (20-30°C) for at least 15 minutes and continue until irritation stops. Make sure to flush under the upper and lower eyelids. If irritation continues, contact a doctor. Continue flushing during transport.

▼ Ingestion

Provide plenty of water for the person to drink and stay with him/her. In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the victim lean forward with head down to avoid inhalation of- or choking on vomited material.

Burns

Rinse with water until the pain stops then continue to rinse for a further 30 minutes.

▼ 4.2. Most important symptoms and effects, both acute and delayed

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

▼ 4.3. Indication of any immediate medical attention and special treatment needed

Nothing special

Information to medics

Bring this safety data sheet.

SECTION 5: Firefighting measures

▼ 5.1. Extinguishing media

Recommended: alcohol-resistant foam, carbonic acid, powder, water mist. Waterjets should not be used, since they can spread the fire.

▼ 5.2. Special hazards arising from the substance or mixture

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous catabolic substances are produced. These are: Carbon oxides. Fire will result in dense black smoke. Exposure to combustion products may harm your health. Fire fighters should wear appropriate protection equipment. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

▼ 5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

SECTION 6: Accidental release measures

▼ 6.1. Personal precautions, protective equipment and emergency procedures

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.

6.2. Environmental precautions

No specific requirements.

▼ 6.3. Methods and material for containment and cleaning up

Use sand, sawdust, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations. To the extent possible cleaning is performed with normal cleaning agents. Avoid use of solvents.

▼ 6.4. Reference to other sections

See section on "Disposal considerations" in regard of handling of waste. See section on 'Exposure controls/personal protection' for protective measures.

SECTION 7: Handling and storage

▼ 7.1. Precautions for safe handling

Avoid static electricity.

Smoking, storage of tobacco, consumption and storage of food or liquids are not allowed in the workrooms. See section on 'Exposure controls/personal protection' for information on personal protection.

▼ 7.2. Conditions for safe storage, including any incompatibilities

Always store in containers of the same material as the original container. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Must be stored in a cool and well-ventilated area, away from possible sources of ignition.

Storage temperature

No data available.

▼ 7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

▼ OEL

carbon dioxide

Long-term exposure limit (8-hour TWA reference period): 5000 ppm | 9150 mg/m³

Short-term exposure limit (15-minute reference period): 15000 ppm | 27400 mg/m³

dimethoxymethan

Long-term exposure limit (8-hour TWA reference period): 1000 ppm | 3160 mg/m³

Short-term exposure limit (15-minute reference period): 1250 ppm | 3950 mg/m³

▼ DNEL / PNEC

DNEL (dimethoxymethan): 132 mg/m³

Exposure: Inhalation

Duration of Exposure: Long term – Systemic effects - Workers

DNEL (dimethoxymethan): 22mg/kg bw/day

Exposure: Dermal

Duration of Exposure: Long term – Systemic effects - Workers

DNEL (dimethoxymethan): 39 mg/m³

Exposure: Inhalation

Duration of Exposure: Long term – Systemic effects - General population

DNEL (dimethoxymethan): 5,7 mg/kg bw/day

Exposure: Dermal

Duration of Exposure: Long term – Systemic effects - General population

DNEL (dimethoxymethan): 9,6 mg/kg bw/day

Exposure: Oral

Duration of Exposure: Long term – Systemic effects - General population

8.2. Exposure controls

▼ Compliance with the accepted occupational exposure limits values should be controlled on a regular basis.

General recommendations

▼ Observe general occupational hygiene standards.

Exposure scenarios

In the event exposure scenarios are appended to the safety data sheet, the operational conditions and risk management measures in these shall be complied with.

▼ Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

▼ Appropriate technical measures

Airborne gas and dust concentrations must be kept at a minimum and below current limit values (see above). Installation of an exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure emergency eyewash and -showers are clearly marked.

▼ Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

▼ Measures to avoid environmental exposure

No specific requirements.

Individual protection measures, such as personal protective equipment



Generally

Use only CE marked protective equipment.

▼ Respiratory Equipment

If ventilation at the work place is insufficient, use a half- or full mask with an appropriate filter or an air-supplied breathing apparatus depending on the specific work situation and how long you will be using the product.

▼ Skin protection

No specific requirements.

▼ Hand protection

Recommended: Nitrile rubber

▼ Eye protection

Wear safety glasses with side shields.

SECTION 9: Physical and chemical properties**▼ 9.1. Information on basic physical and chemical properties**

Form	Aerosol
Colour	White
Odour	Pleasant
Odour threshold (ppm)	No data available.
pH	No data available.
Viscosity (40°C)	No data available.
Density (g/cm ³)	0,85

▼ Phase changes

Melting point (°C)	No data available.
Boiling point (°C)	No data available.
Vapour pressure	No data available.
Decomposition temperature (°C)	No data available.
Evaporation rate (n-butylacetate = 100)	No data available.

▼ Data on fire and explosion hazards

Flash point (°C)	-15
Ignition (°C)	No data available.
Auto flammability (°C)	No data available.
Explosion limits (% v/v)	No data available.
Explosive properties	No data available.

▼ Solubility

Solubility in water	Insoluble
n-octanol/water coefficient	No data available.

▼ 9.2. Other information

Solubility in fat (g/L)	No data available.
-------------------------	--------------------

SECTION 10: Stability and reactivity**10.1. Reactivity**

No data available

▼ 10.2. Chemical stability

The product is stable under the conditions, noted in the section "Handling and storage".

▼ 10.3. Possibility of hazardous reactions

Nothing special

▼ 10.4. Conditions to avoid

Avoid static electricity. Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure.

▼ 10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information**11.1. Information on toxicological effects**

▼ **Acute toxicity**

Substance: carbon dioxide
 Species: Rat
 Test: LC50
 Route of exposure: Inhalation
 Result: 470000 ppm 0,5 h

Substance: dimethoxymethan
 Species: Rabbit
 Test: LD50
 Route of exposure: Dermal
 Result: >500 mg/kg

Substance: dimethoxymethan
 Species: Mouse
 Test: LD50
 Route of exposure: Oral
 Result: 6950 mg/kg

Substance: dimethoxymethan
 Species: Rat
 Test: LD50
 Route of exposure: Oral
 Result: 6423 mg/kg

▼ **Skin corrosion/irritation**

No data available.

Serious eye damage/irritation

No data available.

Respiratory or skin sensitisation

No data available.

Germ cell mutagenicity

No data available.

Carcinogenicity

No data available.

Reproductive toxicity

No data available.

STOT-single exposure

No data available.

STOT-repeated exposure

No data available.

Aspiration hazard

No data available.

▼ **Long term effects**

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

SECTION 12: Ecological information

▼ **12.1. Toxicity**

Substance: dimethoxymethan
 Species: Fish
 Test: LC50
 Duration: 96 h
 Result: >1000 mg/l

Substance: dimethoxymethan
 Species: Daphnia
 Test: LC50
 Duration: 48 h
 Result: >1200mg/l

12.2. Persistence and degradability

Substance	Biodegradability	Test	Result
No data available.			

12.3. Bioaccumulative potential

Substance	Potential bioaccumulation	LogPow	BCF
carbon dioxide	No	0,83	No data available

12.4. Mobility in soil

carbon dioxide: Log Koc= 0,735677, Calculated from LogPow (High mobility potential.).

▼ 12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

▼ 12.6. Other adverse effects

Nothing special

SECTION 13: Disposal considerations**13.1. Waste treatment methods**

Product is covered by the regulations on hazardous waste.

Waste

EWC code

16.05.04

Specific labelling

-

▼ Contaminated packing

Contaminated packaging must be disposed of similarly to the product.

SECTION 14: Transport information**14.1 – 14.4**

This product is within scope of the regulations of transport of dangerous goods.

▼ ADR/RID

14.1. UN number 1950

14.2. UN proper shipping name -

14.3. Transport hazard class(es) 2.1

14.4. Packing group -

Notes -

Tunnel restriction code -

IMDG

UN-no. 1950

Proper Shipping Name Aerosoler

Class 2.1

PG* -

EmS F-D, S-U

MP** NO

Hazardous constituent -

▼ IATA/ICAO

UN-no. 1950

Proper Shipping Name Aerosoler

Class 2.1

PG* -

14.5. Environmental hazards

-

14.6. Special precautions for user

-

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available

(*) Packing group

(**) Marine pollutant

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

▼ Restrictions for application

People under the age of 18 shall not be exposed to this product cf. Council Directive 94/33/EC of 22 June 1994 on the protection of young people at work.

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

Demands for specific education

-

Additional information

Not applicable

Seveso

Seveso III Part 1: P3a

Sources

Council Directive 94/33/EC of 22 June 1994 on the protection of young people at work.

Council Directive 75/324/EEC of 20 May 1975 on the approximation of the laws of the Member States relating to aerosol dispensers.

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677. The Stationery Office, 2002.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (CLP).

EC regulation 1907/2006 (REACH).

The Control of Major Accident Hazards (COMAH) Regulations 2015.

15.2. Chemical safety assessment

No

SECTION 16: Other information**▼ Full text of H-phrases as mentioned in section 3**

H225 - Highly flammable liquid and vapour.

H281 - Contains refrigerated gas; may cause cryogenic burns or injury.

The full text of identified uses as mentioned in section 1

PC24 = Lubricants, Greases and Release Products

PROC 11 = Nonindustrial spraying

SU 10 = Formulation [mixing] of preparations and/or re-packaging (excluding alloys)

SU 22 = Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

ERC2 = Formulation of preparations

AC7 = Metal articles

Additional label elements**Other**

In accordance with Regulation (EC) No. 1272/2008 (CLP) the evaluation of the classification of the mixture is based on:

The classification of the mixture in regard of physical hazards has been based on experimental data.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The safety data sheet is validated by

KAO

**Date of last essential change
(First cipher in SDS version)**

2016-02-10(1.0)

**Date of last minor change
(Last cipher in SDS version)**

2016-02-10

