According to EC-Regulation 2015/830

Pureno Care

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

Universal Grease Product no.

REACH registration number

Not applicable

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

NA

Lubricants, Greases and Release Products (PC24) Nonindustrial spraying (PROC 11) Formulation [mixing] of preparations and/or re-packaging (excluding alloys) (SU 10) Professional uses: Public domain (administration, education, entertainment, services, craftsmen) (SU 22) Formulation of preparations (ERC2) Metal articles (AC7) Uses advised against

The full text of any mentioned and identified use categories are given in section 16

1.3. Details of the supplier of the safety data sheet

Company and address

Pureno A/S Rønnevangs Allé 8 3400 Hillerød Denmark Tlf.: +45 70 260 267 Contact person Kenneth Christensen E-mail

mail@pureno.dk

SDS date

2018-03-21

SDS Version

4.0

1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service). See section 4 "First aid measures".

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Aerosol 3; H229 See full text of H-phrases in section 2.2.

2.2. Label elements

Hazard pictogram(s) Not applicable Signal word Warning Hazard statement(s) Pressurised container: May burst if heated. (H229)

Safety statement(s) General

Keep out of reach of children. (P102).

Prevention	Do not pierce or burn, even after use. (P251).
Response	•
Storage	Protect from sunlight. Do no expose to temperatures exceeding 50 °C/122°F. (P410+P412).
Disposal	
Not applicable 2.3. Other hazards Not applicable Additional labellin	of the contents are flammable

SECTION 3: Composition/information on ingredients

▼3.1/3.2. Substances/Mixtures

NAME: IDENTIFICATION NOS.: CONTENT: CLP CLASSIFICATION:	naphtha (råolie), hydrogenbehandlet tung CAS-no: 64742-48-9 EC-no: 918-481-9 40-60% Asp. Tox. 1 H304
NAME: IDENTIFICATION NOS.: CONTENT: CLP CLASSIFICATION:	Naphtha (petroleum), hydrotreated heavy (0,1 <benzen) CAS-no: 64742-48-9 EC-no: 265-150-3 15 - <25% Flam. Liq. 3, STOT SE 3, Asp. Tox. 1 H226, H304, H336, EUH066</benzen)
NAME: IDENTIFICATION NOS.: CONTENT: CLP CLASSIFICATION: NOTE:	carbon dioxide CAS-no: 124-38-9 EC-no: 204-696-9 5 - <10% Refrig. Liq. Gas H281 L

(*) See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available. L = European occupational exposure limit.

Other information

SECTION 4: First aid measures

4.1. Description of first aid measures

VGeneral information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. The doctor can contact The National Poisons Information Service (dial 111, 24 h service).

Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

VInhalation

Bring the person into fresh air and stay with him/her.

Skin contact

Immediately remove contaminated clothing and shoes. Ensure that skin, which has been exposed to the material, is washed thoroughly with soap and water. Skin cleanser can be used. DO NOT use solvents or thinners.

VEye contact

Remove contact lenses and open eyes widely. Flush eyes with water or saline water(20-30°C) for at least 15 minutes. Seek medical assistance and continue flushing during transport.

Ingestion

Provide plenty of water for the person to drink and stay with him/her. In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting,

unless recommended by the doctor. Have the victim lean forward with head down to avoid inhalation of- or choking on vomited material.

Burns

Not applicable

- 4.2. Most important symptoms and effects, both acute and delayed
 - Nothing special
- **4.3. Indication of any immediate medical attention and special treatment needed** Nothing special

Information to medics

Bring this safety data sheet.

SECTION 5: Firefighting measures

▼5.1. Extinguishing media

Recommended: alcohol-resistant foam, carbonic acid, powder, water mist. Waterjets should not be used, since they can spread the fire.

▼5.2. Special hazards arising from the substance or mixture

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous catabolic substances are produced. These are: Carbon oxides. Fire will result in dense black smoke. Exposure to combustion products may harm your health. Fire fighters should wear appropriate protection equipment. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

▼5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures No specific requirements.

6.2. Environmental precautions

No specific requirements.

V 6.3. Methods and material for containment and cleaning up

Use sand, sawdust, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations. To the extent possible cleaning is performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section on "Disposal considerations" in regard of handling of waste. See section on 'Exposure controls/personal protection' for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid static electricity.

Smoking, storage of tobacco, consumption and storage of food or liquids are not allowed in the workrooms. See section on 'Exposure controls/personal protection' for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Always store in containers of the same material as the original container. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Storage temperature

No data available.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

VOEL

carbon dioxide Long-term exposure limit (8-hour TWA reference period): 5000 ppm | 9150 mg/m³ Short-term exposure limit (15-minute reference period): 15000 ppm | 27400 mg/m³

VDNEL / PNEC

DNEL (Naphtha (petroleum), hydrotreated heavy (0,1<berrean)): 300 mg/kg bw/day Exposure: Dermal Duration of Exposure: Long term – Systemic effects - Workers

Duration of Exposure. Long term – Systemic effects - Workers

DNEL (Naphtha (petroleum), hydrotreated heavy (0,1
benzen)): 1500 mg/m3 Exposure: Inhalation
Duration of Exposure: Long term – Systemic effects - Workers

DNEL (Naphtha (petroleum), hydrotreated heavy (0,1<berren)): 300 mg/kg bw/day Exposure: Dermal Duration of Exposure: Long term – Systemic effects - General population

DNEL (Naphtha (petroleum), hydrotreated heavy (0,1<benzen)): 900 mg/m3 Exposure: Inhalation Duration of Exposure: Long term – Systemic effects - General population

DNEL (Naphtha (petroleum), hydrotreated heavy (0,1
benzen)): 300mg/kg bw/day
Exposure: Oral
Duration of Exposure: Long term – Systemic effects - General population

8.2. Exposure controls

Compliance with the accepted occupational exposure limits values should be controlled on a regular basis. General recommendations

Observe general occupational hygiene standards.

Exposure scenarios

In the event exposure scenarios are appended to the safety data sheet, the operational conditions and risk management measures in these shall be complied with.

VExposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

Airborne gas and dust concentrations must be kept at a minimum and below current limit values (see above). Installation of an exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure emergency eyewash and -showers are clearly marked.

VHygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

Measures to avoid environmental exposure

No specific requirements.

Individual protection measures, such as personal protective equipment



Generally

Use only CE marked protective equipment. Respiratory Equipment No specific requirements. Skin protection No specific requirements. Vhand protection Recommended: Nitrile rubber Eye protection

No specific requirements.

SECTION 9: Physical and chemical properties

$oldsymbol{ abla}$ 9.1. Information on basic physical and chemical properties

Form Colour Odour Odour threshold (ppm) pH Aerosol Brown None No data available. No data available.

Viscosity (40°C) Density (g/cm³) Phase changes Melting point (°C) Boiling point (°C) Vapour pressure Decomposition temperature (°C) Evaporation rate (n-butylacetate = 100) Data on fire and explosion hazards Flash point (°C) Ignition (°C) Auto flammability (°C) Explosion limits (% v/v) **Explosive properties** Solubility Solubility in water n-octanol/water coefficient 9.2. Other information Solubility in fat (g/L)

Pureno Care

No data available. 0,85

No data available. No data available. No data available. No data available. No data available.

42 No data available. No data available. No data available. No data available.

Insoluble No data available.

No data available.

SECTION 10: Stability and reactivity

10.1. Reactivity No data available
✓ 10.2. Chemical stability The product is stable under the conditions, noted in the section "Handling and storage".
✓ 10.3. Possibility of hazardous reactions Nothing special
✓ 10.4. Conditions to avoid Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure.
✓ 10.5. Incompatible materials Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Substance: carbon dioxide Species: Rat Test: LC50 Route of exposure: Inhalation Result: 470000 ppm 0,5 h

Substance: Naphtha (petroleum), hydrotreated heavy (0,1<benzen) Species: Rat Test: LD50 Route of exposure: Dermal Result: >5000mg/kg

Substance: Naphtha (petroleum), hydrotreated heavy (0,1<benzen) Species: Rat Test: LD50 Route of exposure: Oral Result: >5000mg/kg

Substance: Naphtha (petroleum), hydrotreated heavy (0,1<benzen) Species: Rat Test: LC50 Route of exposure: Inhalation Result: >5mg/L

Substance: naphtha (råolie), hydrogenbehandlet tung Species: Rat Test: LD50

According to EC-Regulation 2015/830

Pureno Care

Route of exposure: Dermal Result: >2000 mg/kg

Substance: naphtha (råolie), hydrogenbehandlet tung Species: Rat Test: LD50 Route of exposure: Oral Result: >5000 mg/kg

Substance: naphtha (råolie), hydrogenbehandlet tung Species: Rat Test: LC50 Route of exposure: Inhalation Result: >5000 mg/kg 4 h

Skin corrosion/irritation

No data available. Serious eye damage/irritation No data available.

Respiratory or skin sensitisation No data available. Germ cell mutagenicity No data available. Carcinogenicity No data available. **Reproductive toxicity** No data available. **STOT-single exposure** No data available. **STOT-repeated exposure** No data available. Aspiration hazard No data available. VLong term effects Nothing special

SECTION 12: Ecological information

12.1. Toxicity

Substance: Naphtha (petroleum), hydrotreated heavy (0,1<benzen) Species: Daphnia Test: EC50 Duration: 48 h Result: 1000mg/L

Substance: Naphtha (petroleum), hydrotreated heavy (0,1<benzen) Species: Fish Test: LC50 Duration: 96 h Result: >1000 mg/l

Substance: Naphtha (petroleum), hydrotreated heavy (0,1<benzen) Species: Algae Test: EC50 Duration: Result: >1000mg/l

Substance: naphtha (råolie), hydrogenbehandlet tung Species: Fish Test: LC50 Duration: 96 h Result: >1000 mg/l

Substance: naphtha (råolie), hydrogenbehandlet tung Species: Algae Test: EC50 Duration: Result: >1000 mg/l

Substance: naphtha (råolie), hydrogenbehandlet tung Species: Daphnia Test: EC50

-	uration: 24 h			
	esult: >1000 mg/l ersistence and degr	adability		
S	ubstance aphtha (petroleum),	Biodegradability	Test	Result
hy na	/drotrea aphtha (råolie), /drogenbeha	Yes Yes	No data available Closed Bottle Test	No data available 80
12.3. Bi	oaccumulative pote	ential		
S	ubstance arbon dioxide	Potential bioaccumulation	LogPow 0,83	BCF No data available
c: ▼ 12.5. ⊤ ₽ ▼ 12.6.	Results of PBT and	oc= 0,735677, Calculated from LogI I vPvB assessment does not contain any substances con cts		
SECTION 13	: Disposal consider	ations		
P Was E		nods d by regulations on dangerous waste	Э.	
Oper	asoning			

Contaminated packing Contaminated packaging must be disposed of similarly to the product.

SECTION 14: Transport information

14.1 - 14.4

ADR/RID	
14.1. UN number	1950
14.2. UN proper shipping name	-
14.3. Transport hazard class(es)	2.2
14.4. Packing group	-
Notes	-
Tunnel restriction code	-
IMDG	
UN-no.	1950
Proper Shipping Name	Aerosols
Class	2.2
PG*	-
EmS	F-D, S-U
MP**	NO
Hazardous constituent	-
UN-no.	1950
Proper Shipping Name	Aerosols
Class	2.2
PG*	-

- 14.5. Environmental hazards
- 14.6. Special precautions for user

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code No data available

(*) Packing group (**) Marine pollutant

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

Demands for specific education

Additional information

Not applicable

Seveso

Sources

Council Directive 75/324/EEC of 20 May 1975 on the approximation of the laws of the Member States relating to aerosol dispensers.

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677. The Stationery Office, 2002.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (CLP). EC regulation 1907/2006 (REACH).

15.2. Chemical safety assessment

No

SECTION 16: Other information

VFull text of H-phrases as mentioned in section 3

H226 - Flammable liquid and vapour.

H281 - Contains refrigerated gas; may cause cryogenic burns or injury.

H304 - May be fatal if swallowed and enters airways.

H336 - May cause drowsiness or dizziness.

EUH066 - Repeated exposure may cause skin dryness or cracking.

The full text of identified uses as mentioned in section 1

PC24 = Lubricants, Greases and Release Products

PROC 11 = Nonindustrial spraying

SU 10 = Formulation [mixing] of preparations and/or re-packaging (excluding alloys)

SU 22 = Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- ERC2 = Formulation of preparations
- AC7 = Metal articles

Additional label elements



Other

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The safety data sheet is validated by

KAO

Date of last essential change (First cipher in SDS version) According to EC-Regulation 2015/830

Pureno Care

2016-02-11(3.0) Date of last minor change (Last cipher in SDS version) 2016-02-11

ALPHAOMEGA. Licens nr.:3609221453, 6.4.0.12 www.chymeia.com