

# SAFETY DATA SHEET

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Trade name**

Zink spray

**Product no.**

-

**REACH registration number**

Not applicable

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses of the substance or mixture**

NA

Metal surface treatment products, including galvanic and electroplating products, (PC14)

Non industrial spraying (PROC 11)

Formulation [mixing] of preparations and/or re-packaging (excluding alloys) (SU 10)

Professional uses: Public domain (administration, education, entertainment, services, craftsmen) (SU 22)

Formulation of preparations (ERC2)

Metal articles (AC7)

**Uses advised against**

-

The full text of any mentioned and identified use categories are given in section 16

### 1.3. Details of the supplier of the safety data sheet

**Company and address**

Pureno A/S

Rønnevangs Allé 8

3400 Hillerød

Denmark

Tlf.: +45 70 260 267

**Contact person**

Kenneth Christensen

**E-mail**

mail@pureno.dk

**SDS date**

2018-02-20

**SDS Version**

5.0

### 1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service). See section 4 "First aid measures".

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

Aerosol 1; H222, H229

Skin Irrit. 2; H315

Aquatic Acute 1; H400

Aquatic Chronic 1; H410

See full text of H-phrases in section 2.2.

### 2.2. Label elements

**Hazard pictogram(s)**

**Signal word**

Danger

**Hazard statement(s)**

Extremely flammable aerosol. (H222)  
 Pressurised container: May burst if heated. (H229)  
 Causes skin irritation. (H315)  
 Very toxic to aquatic life with long lasting effects. (H410)

**Safety statement(s)**

**General** If medical advice is needed, have product container or label at hand. (P101).  
 Keep out of reach of children. (P102).  
**Prevention** Do not pierce or burn, even after use. (P251).  
**Response** Collect spillage. (P391).  
**Storage** Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.  
 (P410+P412).  
**Disposal** Dispose of contents/container to an approved waste disposal plant. (P501).

**▼ Identity of the substances primarily responsible for the major health hazards**

Not applicable

**2.3. Other hazards**

This product contains an organic solvent. Repeated or prolonged exposure to organic solvents may result in adverse effects to the nervous system and internal organs such as liver and kidneys.

**▼ Additional labelling**

Not applicable

**▼ Additional warnings**

Not applicable

**VOC**

Not applicable

**SECTION 3: Composition/information on ingredients****▼ 3.1/3.2. Substances/Mixtures**

NAME:	propan-1-flydende-tilstand
IDENTIFICATION NOS.:	CAS-no: 74-98-6 EC-no: 200-827-9 Index-no: 601-003-00-5
CONTENT:	25-40%
CLP CLASSIFICATION:	Press. Gas H220
NAME:	zinc powder - zinc dust (pyrophoric)
IDENTIFICATION NOS.:	CAS-no: 7440-66-6 EC-no: 231-175-3 Index-no: 030-001-00-1
CONTENT:	25-40%
CLP CLASSIFICATION:	Flam. Sol. 1, Aquatic Acute 1, Aquatic Chronic 1 H228, H400, H410 (M-acute = 1) (M-chronic = 1)
NAME:	but-1-en
IDENTIFICATION NOS.:	CAS-no: 106-97-8 EC-no: 203-448-7 Index-no: 601-004-00-0
CONTENT:	15 - <25%
CLP CLASSIFICATION:	Flam. Gas 1 H220
NAME:	isobutan
IDENTIFICATION NOS.:	CAS-no: 75-28-5 EC-no: 200-857-2 Index-no: 601-004-00-0
CONTENT:	15 - <25%
CLP CLASSIFICATION:	Comp. Gas, Flam. Gas 1 H220, H280
NAME:	xylene, blanding af isomerer, kemisk rent
IDENTIFICATION NOS.:	CAS-no: 1330-20-7 EC-no: 215-535-7 Index-no: 601-022-00-9
CONTENT:	5 - <10%
CLP CLASSIFICATION:	Flam. Liq. 2, Acute Tox. 4, Skin Irrit. 2 H225, H312, H315, H332

NOTE:	SL
NAME:	2-methylbutan
IDENTIFICATION NOS.:	CAS-no: 78-78-4 EC-no: 201-142-8 Index-no: 601-006-00-1
CONTENT:	2.5 - <5%
CLP CLASSIFICATION:	Flam. Liq. 1, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2 H224, H304, H336, H411, EUH066
NOTE:	SL

(\*) See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.  
S = Organic solvent L = European occupational exposure limit.

### Other information

ATEmix(inhale, vapour) > 20  
 ATEmix(inhale, dust/mist) > 5  
 ATEmix(inhale, gas) > 20000  
 ATEmix(dermal) > 2000  
 ATEmix(oral) > 2000  
 Skin Cat. 2 Sum =  $\sum(Ci/S(G)CLi) = 0,56 - 0,84$   
 N chronic (CAT 1) Sum =  $\sum(Ci/(M(chronic)^{i*25})) = 1,12 - 1,68$   
 N acute (CAT 1) Sum =  $\sum(Ci/M(acute)^{i*25}) = 1,12 - 1,68$

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### ▼ General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. The doctor can contact The National Poisons Information Service (dial 111, 24 h service). Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

#### ▼ Inhalation

Bring the person into fresh air and stay with him/her.

#### ▼ Skin contact

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with soap and water. Skin cleanser can be used. DO NOT use solvents or thinners.

#### ▼ Eye contact

Remove contact lenses and open eyes widely. Flush eyes with water or saline water(20-30°C) for at least 15 minutes. Seek medical assistance and continue flushing during transport.

#### Ingestion

Provide plenty of water for the person to drink and stay with him/her. In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the victim lean forward with head down to avoid inhalation of- or choking on vomited material.

#### Burns

Rinse with water until the pain stops then continue to rinse for a further 30 minutes.

### 4.2. Most important symptoms and effects, both acute and delayed

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

### ▼ 4.3. Indication of any immediate medical attention and special treatment needed

Nothing special

#### Information to medics

Bring this safety data sheet.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Recommended: alcohol-resistant foam, carbonic acid, powder, water mist. Waterjets should not be used, since they can spread the fire.

**5.2. Special hazards arising from the substance or mixture**

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous catabolic substances are produced. These are: Carbon oxides. Fire will result in dense black smoke. Exposure to combustion products may harm your health. Fire fighters should wear appropriate protection equipment. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

**5.3. Advice for firefighters**

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.

**6.2. Environmental precautions**

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities. It is recommended to install waste collection trays to prevent emissions to the waste water system and surrounding environment.

**6.3. Methods and material for containment and cleaning up**

Use sand, sawdust, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations. To the extent possible cleaning is performed with normal cleaning agents. Avoid use of solvents.

**6.4. Reference to other sections**

See section on "Disposal considerations" in regard of handling of waste. See section on 'Exposure controls/personal protection' for protective measures.

**SECTION 7: Handling and storage****7.1. Precautions for safe handling**

Avoid static electricity.  
Smoking, storage of tobacco, consumption and storage of food or liquids are not allowed in the workrooms. It is recommended to install waste collection trays to prevent emissions to the waste water system and surrounding environment. See section on 'Exposure controls/personal protection' for information on personal protection.

**7.2. Conditions for safe storage, including any incompatibilities**

Always store in containers of the same material as the original container. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Must be stored in a cool and well-ventilated area, away from possible sources of ignition.

**Storage temperature**

No data available.

**7.3. Specific end use(s)**

This product should only be used for applications quoted in section 1.2

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****OEEL**

2-methylbutan

Long-term exposure limit (8-hour TWA reference period): 600 ppm | 1800 mg/m<sup>3</sup>

Short-term exposure limit (15-minute reference period): - ppm | - mg/m<sup>3</sup>

xylene, blending of isomers, kerosene

Long-term exposure limit (8-hour TWA reference period): 50 ppm | 220 mg/m<sup>3</sup>

Short-term exposure limit (15-minute reference period): 100 ppm | 441 mg/m<sup>3</sup>

Comments: Sk BMGV (Bmgv = Biological Monitoring Guidance Value. Sk = Can be absorbed through skin. )

but-1-en

Long-term exposure limit (8-hour TWA reference period): 600 ppm | 1450 mg/m<sup>3</sup>

Short-term exposure limit (15-minute reference period): 750 ppm | 1810 mg/m<sup>3</sup>

Comments: Carc (>0,1%butadien) (Carc = Capable of causing cancer. )

**DNEL / PNEC**

DNEL (xylene, blending of isomers, kerosene): 289 mg/m<sup>3</sup>

Exposure: Inhalation  
 Duration of Exposure: Short term – Local effects - Workers

DNEL (xylen, blanding af isomerer, kemisk rent): 180 mg/kg bw/day  
 Exposure: Dermal  
 Duration of Exposure: Long term – Systemic effects - Workers

DNEL (xylen, blanding af isomerer, kemisk rent): 77 mg/m3  
 Exposure: Inhalation  
 Duration of Exposure: Long term – Systemic effects - Workers

DNEL (xylen, blanding af isomerer, kemisk rent): 174 mg/m3  
 Exposure: Inhalation  
 Duration of Exposure: Short term – Local effects - General population

DNEL (xylen, blanding af isomerer, kemisk rent): 14,8 mg/m3  
 Exposure: Inhalation  
 Duration of Exposure: Long term – Systemic effects - General population

DNEL (xylen, blanding af isomerer, kemisk rent): 108 mg/kg bw/day  
 Exposure: Dermal  
 Duration of Exposure: Long term – Systemic effects - General population

**8.2. Exposure controls**

▼ Compliance with the accepted occupational exposure limits values should be controlled on a regular basis.

**General recommendations**

Observe general occupational hygiene standards.

**Exposure scenarios**

In the event exposure scenarios are appended to the safety data sheet, the operational conditions and risk management measures in these shall be complied with.

▼ **Exposure limits**

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

▼ **Appropriate technical measures**

Airborne gas and dust concentrations must be kept at a minimum and below current limit values (see above). Installation of an exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure emergency eyewash and -showers are clearly marked.

**Hygiene measures**

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

▼ **Measures to avoid environmental exposure**

Keep containment materials near the workplace. If possible, collect spillage during work.

**Individual protection measures, such as personal protective equipment**



**Generally**

Use only CE marked protective equipment.

**Respiratory Equipment**

Recommended: AX. Brown

**Skin protection**

Wear appropriate protection clothing, e.g. coveralls in polypropylene approved type 6 and Category III.

**Hand protection**

Recommended: Nitrile rubber

**Eye protection**

Wear safety glasses with side shields.

**SECTION 9: Physical and chemical properties**

▼ **9.1. Information on basic physical and chemical properties**

Form	Aerosol
Colour	Gray
Odour	Characteristic
Odour threshold (ppm)	No data available.
pH	No data available.
Viscosity (40°C)	No data available.
Density (g/cm <sup>3</sup> )	No data available.
<b>Phase changes</b>	
Melting point (°C)	No data available.
Boiling point (°C)	No data available.
Vapour pressure	No data available.
Decomposition temperature (°C)	No data available.
Evaporation rate (n-butylacetate = 100)	No data available.
<b>Data on fire and explosion hazards</b>	
Flash point (°C)	-25
Ignition (°C)	No data available.
Auto flammability (°C)	No data available.
Explosion limits (% v/v)	No data available.
Explosive properties	No data available.
<b>Solubility</b>	
Solubility in water	Insoluble
n-octanol/water coefficient	No data available.
<b>9.2. Other information</b>	
Solubility in fat (g/L)	No data available.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No data available

### 10.2. Chemical stability

The product is stable under the conditions, noted in the section "Handling and storage".

### ▼ 10.3. Possibility of hazardous reactions

Nothing special

### ▼ 10.4. Conditions to avoid

Avoid static electricity. Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure.

### 10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

### 10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### ▼ Acute toxicity

Substance: xylen, blanding af isomerer, kemisk rent

Species: Rabbit

Test: LD50

Route of exposure: Dermal

Result: >1100 mg/kg

Substance: xylen, blanding af isomerer, kemisk rent

Species: Rat

Test: LD50

Route of exposure: Oral

Result: 4300 mg/kg

Substance: xylen, blanding af isomerer, kemisk rent

Species: Rat

Test: LC50

Route of exposure: Inhalation

Result: 5000 ppm(4hours)

#### ▼ Skin corrosion/irritation

Causes skin irritation.

**Serious eye damage/irritation**

No data available.

**Respiratory or skin sensitisation**

No data available.

**Germ cell mutagenicity**

No data available.

**Carcinogenicity**

No data available.

**Reproductive toxicity**

No data available.

**STOT-single exposure**

No data available.

**STOT-repeated exposure**

No data available.

**Aspiration hazard**

No data available.

**Long term effects**

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

**SECTION 12: Ecological information**

▼ **12.1. Toxicity**

Substance: 2-methylbutan  
 Species: Fish  
 Test: LC50  
 Duration: 96 h  
 Result: 12,8mg/l

Substance: 2-methylbutan  
 Species: Daphnia  
 Test: EC50  
 Duration: 48 h  
 Result: 2,3 mg/l

Substance: xylen, blanding af isomerer, kemisk rent  
 Species: Fish  
 Test: LC50  
 Duration: 96 h  
 Result: 13,5 mg/l

Substance: xylen, blanding af isomerer, kemisk rent  
 Species: Algae  
 Test: EC50  
 Duration: 72 h  
 Result: 3,2 mg/l

Substance: xylen, blanding af isomerer, kemisk rent  
 Species: Daphnia  
 Test: EC50  
 Duration: 48 h  
 Result: 3,2 mg/l

Substance: isobutan  
 Species: Algae  
 Test: EC50  
 Duration: 72 h  
 Result: 8,6 mg/l

Substance: isobutan  
 Species: Daphnia  
 Test: EC50  
 Duration: 48 h  
 Result: 16,3 mg/l

Substance: isobutan  
 Species: Fish  
 Test: LC50  
 Duration: 96 h  
 Result: 28 mg/kg

▼ **12.2. Persistence and degradability**

Substance	Biodegradability	Test	Result
2-methylbutan	Yes	No data available	71,43%
xylen, blanding af isomerer, k...	Yes	Manometric Respirometry Test	87,8%
isobutan	Yes	No data available	No data available

▼ **12.3. Bioaccumulative potential**

Substance	Potential bioaccumulation	LogPow	BCF
2-methylbutan	No	No data available	No data available
xylen, blanding af isomerer, k...	Yes	3,16	No data available
isobutan	No	No data available	No data available

▼ **12.4. Mobility in soil**

xylen, blanding af isomerer, k...: Log Koc= 2,580804, Calculated from LogPow (Moderate mobility potential.).

▼ **12.5. Results of PBT and vPvB assessment**

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

▼ **12.6. Other adverse effects**

This product contains substances that are toxic to the environment. May result in adverse effects to aquatic organisms.

This product contains substances, which due to poor biodegradability, may cause adverse long-term effects to the aquatic environment,

This product contains substances with the potential of bioaccumulation resulting in the risk of accumulation in the food chain. Bioaccumulative substances are concentrated in adipose tissue and are not easily secreted.

**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**

Product is covered by the regulations on hazardous waste.

**Waste**

EWC code  
 16.05.05

**Specific labelling**

-

▼ **Contaminated packing**

Contaminated packaging must be disposed of similarly to the product.

**SECTION 14: Transport information**

**14.1 – 14.4**

This product is within scope of the regulations of transport of dangerous goods.

**ADR/RID**

14.1. UN number	1950
14.2. UN proper shipping name	-
14.3. Transport hazard class(es)	2.1
14.4. Packing group	-
Notes	-
Tunnel restriction code	-

**IMDG**

UN-no.	1950
Proper Shipping Name	Aerosols
Class	2.1
PG*	-
EmS	F-D, S-U
MP**	Yes



<b>Hazardous constituent</b>	-
<b>IATA/CAO</b>	
<b>UN-no.</b>	1950
<b>Proper Shipping Name</b>	Aerosols
<b>Class</b>	2.1
<b>PG*</b>	-

#### 14.5. Environmental hazards

This product contains substances, which due to poor biodegradability, may cause adverse long-term effects to the aquatic environment,

#### 14.6. Special precautions for user

-

#### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available

(\*) Packing group

(\*\*) Marine pollutant

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### Restrictions for application

People under the age of 18 shall not be exposed to this product cf. Council Directive 94/33/EC of 22 June 1994 on the protection of young people at work.

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

##### Demands for specific education

-

##### Additional information

Not applicable

##### Seveso

Seveso III Part 1: P3a, E1

##### Sources

Council Directive 92/85/EEC on the introduction of measures to encourage improvements in the safety and health at work of pregnant workers and workers who have recently given birth or are breastfeeding.

Council Directive 94/33/EC of 22 June 1994 on the protection of young people at work.

Council Directive 75/324/EEC of 20 May 1975 on the approximation of the laws of the Member States relating to aerosol dispensers.

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677. The Stationery Office, 2002.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (CLP).

EC regulation 1907/2006 (REACH).

The Control of Major Accident Hazards (COMAH) Regulations 2015.

#### 15.2. Chemical safety assessment

No

### SECTION 16: Other information

#### Full text of H-phrases as mentioned in section 3

H220 - Extremely flammable gas.

H224 - Extremely flammable liquid and vapour.

H225 - Highly flammable liquid and vapour.

H228 - Flammable solid.

H280 - Contains gas under pressure; may explode if heated.

H304 - May be fatal if swallowed and enters airways.

H312 - Harmful in contact with skin.

H315 - Causes skin irritation.

H332 - Harmful if inhaled.

- H336 - May cause drowsiness or dizziness.
- H400 - Very toxic to aquatic life.
- H410 - Very toxic to aquatic life with long lasting effects.
- H411 - Toxic to aquatic life with long lasting effects.
- EUH066 - Repeated exposure may cause skin dryness or cracking.

**The full text of identified uses as mentioned in section 1**

- PC14 = Metal surface treatment products, including galvanic and electroplating products,
- PROC 11 = Non industrial spraying
- SU 10 = Formulation [mixing] of preparations and/or re-packaging (excluding alloys)
- SU 22 = Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- ERC2 = Formulation of preparations
- AC7 = Metal articles

**Additional label elements**



**Other**

In accordance with Regulation (EC) No. 1272/2008 (CLP) the evaluation of the classification of the mixture is based on:

- The classification of the mixture in regard of physical hazards has been based on experimental data.
- The classification of the mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP)
- The classification of the mixture in regard of environmental hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP)

The classification of the mixture in regard of skin corrosion and serious eye damage is based on the pH-criterion given by Regulation (EC) No. 1272/2008 (CLP) It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

**The safety data sheet is validated by**

KAO

**Date of last essential change  
(First cipher in SDS version)**

2017-01-17(4.0)

**Date of last minor change  
(Last cipher in SDS version)**

2017-01-17