

Printing date 08.02.2019 Version number 5 Revision: 08.02.2019

### **SECTION 1: Identification of the substance/mixture and of the company/undertaking**

- · 1.1 Product identifier
- · Trade name: Gasket Silicone
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

SU21 Consumer uses: Private households / general public / consumers

· Application of the substance / the mixture

One component temperature resistant silicone sealing for high temperature application

- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Pureno A/S

Rønnevangs Alle 8

3400 Hillerød

+45 70 260 261

Pureno.dk

mail@pureno.dk

· 1.4 Emergency telephone number: +45 82 121 121

## **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

The product is tested according 92/69/EC and is not classified as irritating to skin and eyes.

Aerosol 3 H229 Pressurised container: May burst if heated.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

- · Hazard pictograms Void
- · Signal word Warning
- · Hazard statements

H229 Pressurised container: May burst if heated.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

- · 2.3 Other hazards not applicable
- · Results of PBT and vPvB assessment
- · PBT:

540-97-6 dodecamethylcyclohexasiloxane (D6)

· vPvB:

540-97-6 dodecamethylcyclohexasiloxane (D6)

### **SECTION 3: Composition/information on ingredients**

- · 3.2 Chemical characterisation: Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

(Contd. on page 2)

Page 1/9

Printing date 08.02.2019 Version number 5 Revision: 08.02.2019

**Trade name: Gasket Silicone** 

		(Contd. of page 1
· Dangerous components:		
CAS: 29118-24-9	trans-1,3,3,3-Tetrafluoroprop-1-ene	1-2.5%
ELINCS: 471-480-0	Press. Gas C, H280	
Reg.nr.: 01-0000019758-54-xxxx		
CAS: 4253-34-3	methylsilanetriyl triacetate	1-2.5%
EINECS: 224-221-9	Skin Corr. 1B, H314; <b>(1)</b> Acute Tox. 4, H302	
Reg.nr.: 01-2119962266-32-xxxx		
CAS: 17865-07-5	Propyltriacetoxysilan	1-2.5%
EINECS: 241-816-9	Skin Corr. 1B, H314	
Reg.nr.: 01-2119966899-07-xxxx		
CAS: 540-97-6	dodecamethylcyclohexasiloxane (D6)	<1%
EINECS: 208-762-8	Non-classified vPvB substance.	
Reg.nr.: 01-2119517435-42-xxx	Non-classified PBT substance.	
· SVHC		
540-97-6 dodecamethylcyclohexa	asiloxane (D6)	
Additional information: For the	wording of the listed hazard phrases refer to section 16.	

## **SECTION 4: First aid measures**

- · 4.1 Description of first aid measures
- · General information:

In case of accident or if you feel unwell, seek medical advice (show label or MSDS if possible).

- · After inhalation: No treatment necessary if the product is used normally.
- · After skin contact:

Treat affected skin with cotton wool or cellulose. Then wash and rinse thoroughly with water and a mild cleaning agent.

· After eye contact:

Rinse opened eye for several minutes under running water. Remove contact lenses, if present and easy to do. Continue rinsing. Then consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray.

Foam

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

Danger of bursting by heating.

In case of fire, the following can be released:

Carbon monoxide (CO)

- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.
- · Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Cool endangered receptacles with water spray and remove it out of emergency area if possible.

GB

Printing date 08.02.2019 Version number 5 Revision: 08.02.2019

Trade name: Gasket Silicone

(Contd. of page 2)

### **SECTION 6: Accidental release measures**

### · 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective clothing.

Particular danger of slipping on leaked/spilled product.

#### · 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

#### · 6.3 Methods and material for containment and cleaning up:

Pick up mechanically.

Dispose of the material collected according to regulations.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

### · 6.4 Reference to other sections

No dangerous substances are released.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## **SECTION 7: Handling and storage**

### · 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care.

### · Information about fire - and explosion protection:

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store only in the original receptacle.

Do not store in gangways or stairways.

Store in a cool location under dry conditions in well sealed receptacles

Observe official regulations on storing packagings with pressurised containers.

· Information about storage in one common storage facility:

Do not store together with oxidizing and selfigniting materials.

· Further information about storage conditions:

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

Do not store together with oxidizing and selft-igniting material.

### **SECTION 8: Exposure controls/personal protection**

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

During the curing small amount of acetic acid will be released.

· DNELs		
29118-24-	9 trans-1,3,3,3-Tetraflu	oroprop-1-ene
Inhalative	wrks, long, system	3,902 mg/m³ (mouse)
	cstm, long, system	830 mg/m³ (mouse)
4253-34-3	methylsilanetriyl triace	etate
Oral	cstm, long, system, oral	1 mg/kg/d (mouse)
	cstm, short, system	1 mg/kg bw/d (rabbit)
Dermal	wrks, long, system	14.5 mg/kg/d (mouse)

(Contd. on page 4)

Printing date 08.02.2019 Version number 5 Revision: 08.02.2019

Trade name: Gasket Silicone

		(Contd. of pag
	cstm, long, system	7.2 mg/kg/d (mouse)
	wrks, short, system	
T 1 1 .	cstm, short, system	
Inhalative	wrks, long, system	25 mg/m³ (mouse)
	cstm, long, system	6.3 mg/m³ (mouse)
	wrks, short, system	
	wrks, long, local	31 mg/m³ (rabbit)
	cstm, long, local	5.1 mg/m³ (mouse)
	estm, short, local	5.1 mg/m³ (rabbit)
	cstm, short, system	
	wrks, short, local	31 mg/m³ (mouse)
	5 Propyltriacetoxy	
Oral	cstm, long, system.	
Dermal	wrks, long, system	12.11 mg/kg/d (mouse)
	cstm, long, system	6.05 mg/kg/d (rabbit)
Inhalative	wrks, long, system	85.39 mg/m³ (mouse)
	cstm, long, system	21.06 mg/m³ (rabbit)
PNECs		
		rafluoroprop-1-ene
Oral fresh		0.1 mg/l (daphnia)
	methylsilanetriyl	
Oral fresh		1 mg/l (daphnia)
	nent (fresh water)	3.4 mg/(kg dw) (daphnia)
STP		10 mg/l (daphnia)
soil		0.145 mg/(kg dw) (daphnia)
sedin	nent (marine water)	0.34 mg/(kg bw) (daphnia)
	ne water	0.1 mg/l (daphnia)
intermittent release 1		10 mg/l (daphnia)
	5 Propyltriacetoxy	
Oral fresh		0.02441 mg/l (daphnia)
	nent (fresh water)	0.01457 mg/(kg dw) (daphnia)
STP		10.55 mg/l (daphnia)
soil		0.00336 mg/(kg dw) (daphnia)
sedin	nent (marine water)	0.001457 mg/(kg bw) (daphnia)
marine water 0.0		0.002441 mg/l (daphnia)
Additiona	l Occupational Ex	posure Limit Values for possible hazards during processing:
	etic acid	
		rm value: 50 mg/m <sup>3</sup> , 20 ppm
WEL (Gre		
	Long-te	rm value: 25 mg/m³, 10 ppm rm value: 50 mg/m³, 20 ppm

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Do not eat, drink, smoke or sniff while working.

Wash hands before breaks and at the end of work.

(Contd. on page 5)

(Contd. of page 4)

# Safety data sheet according to 1907/2006/EC, Annex II

Printing date 08.02.2019 Version number 5 Revision: 08.02.2019

Trade name: Gasket Silicone

· Respiratory protection:

Not necessary if room is well-ventilated.

Short term filter device:

Filter A/P2

## · Protection of hands:

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

### · Material of gloves

Recommended thickness of the material:  $\geq 0.5$  mm

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

## · Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eye protection: Goggles recommended during refilling
- · Body protection: Protective work clothing

<b>SECTION 9: Ph</b>	vsical and	chemical	properties
	y brear arra	CHCHILCUI	properties

5201101(7711) stem und enomical properties		
· 9.1 Information on basic physical and c	hemical properties	
· General Information	• •	
· Appearance:		
Form:	paste-like	
Colour:	Black	
· Odour:	Like aromates	
· Odour threshold:	Not determined.	
· pH-value:	Not determined.	
· Change in condition		
Melting point/freezing point:	Undetermined.	
Initial boiling point and boiling range	: Not applicable, as aerosol.	
· Flash point:	Not applicable, as aerosol.	
· Flammability (solid, gas):	Not applicable.	
· Decomposition temperature:	Not determined.	
· Auto-ignition temperature:	Product is not selfigniting.	
· Explosive properties:	Product does not present an explosion hazard.	
· Explosion limits:		
Lower:	3.0 %	
Upper:	16 %	
· Vapour pressure:	Not applicable.	
· Density at 20 °C:	1.03 g/cm <sup>3</sup>	
· Relative density	Not determined.	
· Vapour density	Not determined.	
· Evaporation rate	Not applicable.	
· Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	

(Contd. on page 6)

Printing date 08.02.2019 Version number 5 Revision: 08.02.2019

**Trade name: Gasket Silicone** 

(Contd. of page 5)

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

**Dynamic:** Not determined. **Kinematic:** Not determined.

 Organic solvents:
 0.0 %

 VOC (EC)
 0.0 g/l

 VOC (EU)
 0.00 %

 VOCV (CH)
 0.00 %

• **9.2 Other information** No further relevant information available.

## **SECTION 10: Stability and reactivity**

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions Danger of bursting.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No decomposition if used according to specifications.

## **SECTION 11: Toxicological information**

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

## 4253-34-3 methylsilanetriyl triacetate

Oral LD50 1,600 mg/kg (rat)

- · Primary irritant effect:
- · Skin corrosion/irritation

No irritant effect.

test system/specie: rabbit

· Serious eye damage/irritation

No irritant effect.

test system/specie: rabbit

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

## **SECTION 12: Ecological information**

- · 12.1 Toxicity No further relevant informations available.
- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

(Contd. on page 7)

Printing date 08.02.2019 Version number 5 Revision: 08.02.2019

**Trade name: Gasket Silicone** 

· 12.5 Results of PBT and vPvB assessment

(Contd. of page 6)

- · PBT:
- 540-97-6 dodecamethylcyclohexasiloxane (D6)
- · vPvB:
- 540-97-6 dodecamethylcyclohexasiloxane (D6)
- 12.6 Other adverse effects No further relevant information available.

# **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue	
08 04 10	waste adhesives and sealants other than those mentioned in 08 04 09
16 05 04*	gases in pressure containers (including halons) containing hazardous substances
15 01 04	metallic packaging

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 1	4: Transport	information

· 14.1	<b>UN-Number</b>
--------	------------------

· ADR, IMDG, IATA UN1950

· 14.2 UN proper shipping name

· ADR 1950 AEROSOLS · IMDG AEROSOLS

· IATA AEROSOLS, non-flammable

- · 14.3 Transport hazard class(es)
- · ADR



· Class 2 5A Gases.

· Label 2.2

· IMDG, IATA



· Class 2.2 · Label 2.2

· 14.4 Packing group

· ADR, IMDG, IATA Void

· 14.5 Environmental hazards:

· Marine pollutant: No

• 14.6 Special precautions for user Warning: Gases.

· Danger code (Kemler):

• **EMS Number:** F-D,S-U

· Stowage Code SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1

(Contd. on page 8)

Printing date 08.02.2019 Version number 5 Revision: 08.02.2019

Trade name: Gasket Silicone

	(Contd. of page 7
· Segregation Code	litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.  SG69 For AEROSOLS with a maximum capacity of litre: Segregation as for class 9. Stow "separated from class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS Segregation as for the appropriate subdivision of class 2.
· 14.7 Transport in bulk according to A Marpol and the IBC Code	Annex II of Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
· Transport category	3
· Tunnel restriction code	E
	(Dangerous goods in "LQ" with more than 8 tons gros mass of LQ falls under the tunnel restriction code "E")
· IMDG	·
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
	UN 1950 AEROSOLS, 2.2

## **SECTION 15: Regulatory information**

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · National regulations:
- · Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · Other regulations, limitations and prohibitive regulations
- · Substances of very high concern (SVHC) according to REACH, Article 57

540-97-6 dodecamethylcyclohexasiloxane (D6)

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

## · Relevant phrases

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

### · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

(Contd. on page 9)

(Contd. of page 8)

# Safety data sheet according to 1907/2006/EC, Annex II

Printing date 08.02.2019 Version number 5 Revision: 08.02.2019

#### Trade name: Gasket Silicone

ICAO: International Civil Aviation Organisation

ctsm, long, system: general population, long-term exposure, systematic effects

cstm, short, system: general population, acute / short-term exposure, systematic effects

wrks, long, system: workers, long-term exposure - systemic effects

wrks, short, system: workers, acute / short-term exposure - systemic effects

cstm, long, local: general population, long-term exposure, local effects

STP: sewage treatment plant

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOCV: Lenkungsabgabe auf flüchtigen organischen Verbindungen, Schweiz (Swiss Ordinance on volatile organic compounds)

VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Aerosol 3: Aerosols – Category 3

Press. Gas C: Gases under pressure – Compressed gas

Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1B: Skin corrosion/irritation - Category 1B

\* \* Data compared to the previous version altered.