SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name
IDZ Rapid A
Product no.
9
REACH registration number
Not applicable

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture
Desinfectant for the food industry
Biocidal Products (e.g. Disinfectants, pest control) (PC8)
Manufacture of food products (SU 4)
Wide dispersive indoor use of processing aids in open systems (ERC8a)
Uses advised against
-
The full text of any mentioned and identified use categories are given in section 16

1.3. Details of the supplier of the safety data sheet

Company and address
Pureno
Rønnevangs Allé 8
DK - 3400 Hillerød
Tlf.: 70260267
mail@pureno.dk
Contact person
Mette Borg
E-mail
mb@iduna.dk
SDS date
2020-03-05
SDS Version
1.0

1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service). See section 4 “First aid measures”.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Flam. Liq. 2; H225
Eye Irrit. 2; H319
See full text of H-phrases in section 2.2.

2.2. Label elements

Hazard pictogram(s)

Signal word
Danger
Hazard statement(s)

Highly flammable liquid and vapour. (H225)
Causes serious eye irritation. (H319)

Precautionary statements

General	-
Prevention	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. (P210). Wear eye protection. (P280).
Response	If eye irritation persists: Get medical advice/attention. (P337+P313). In case of fire: Use alcohol-resistant foam/carbonic acid/powder/water mist/carbon dioxide/dry sand to extinguish. (P370+P378).
Storage	Store in a well-ventilated place. Keep cool. (P403+P235).
Disposal	Dispose of contents/container to an approved waste disposal plant. (P501).

Identity of the substances primarily responsible for the major health hazards

Not applicable

Additional labelling

Not applicable

Unique formula identifier (UFI)

-

2.3. Other hazards

Highly flammable liquid. Causes serious eye irritation. The product releases vapors from organic solvents that can cause drowsiness and dizziness. At high concentrations, the fumes can cause headaches and intoxication.

Additional warnings

Not applicable

VOC (volatile organic compound)

Not applicable

SECTION 3: Composition/information on ingredients

3.1/3.2. Substances/Mixtures

NAME:	ethanol ethyl alcohol
IDENTIFICATION NOS.:	CAS-no: 64-17-5 EC-no: 200-578-6 REACH-no: 01-2119457610-43-XXXX Index-no: 603-002-00-5
CONTENT:	60-80%
CLP CLASSIFICATION:	Flam. Liq. 2, Eye Irrit. 2 H225, H319
NOTE:	O

NAME:	propan-2-ol isopropyl alcohol isopropanol
IDENTIFICATION NOS.:	CAS-no: 67-63-0 EC-no: 200-661-7 REACH-no: 01-2119457558-25-XXXX Index-no: 603-117-00-0
CONTENT:	5 - <10%
CLP CLASSIFICATION:	Flam. Liq. 2, STOT SE 3, Eye Irrit. 2 H225, H319, H336
NOTE:	O

(*) See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.
O = Organic solvent

Other information

ATEmix(dermal) > 2000
ATEmix(oral) > 2000
Eye Cat. 2 Sum = Sum(Ci/S(G)CLi) = 1,792 - 2,688
N acute (CAT 1) Sum = Sum(Ci/M(acute)i*25) = 0,08 - 0,12

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. The doctor can contact The National Poisons Information Service: Dial 0344 892 0111 (24 h service). Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an

unconscious person water or other drink.

Inhalation

Bring the person into fresh air and stay with him/her.

Skin contact

Immediately remove contaminated clothing and shoes. Ensure that skin, which has been exposed to the material, is washed thoroughly with soap and water.

Eye contact

Remove contact lenses. Flush eyes immediately with plenty of water or isotonic water (20-30°C) for at least 15 minutes and continue until irritation stops. Make sure to flush under the upper and lower eyelids. If irritation continues, contact a doctor. Continue flushing during transport.

Ingestion

Provide plenty of water for the person to drink and stay with him/her. In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the victim lean forward with head down to avoid inhalation of- or choking on vomited material.

Burns

Rinse with water until the pain stops then continue to rinse for a further 30 minutes.

4.2. Most important symptoms and effects, both acute and delayed

Causes serious eye irritation. The product releases vapors from organic solvents that can cause drowsiness and dizziness. At high concentrations, the fumes can cause headaches and intoxication. Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

4.3. Indication of any immediate medical attention and special treatment needed

If eye irritation persists: Get medical advice/attention.

Information to medics

Bring this safety data sheet.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Recommended: alcohol-resistant foam, carbonic acid, powder, water mist. Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous catabolic substances are produced. These are: Carbon oxides. Fire will result in dense black smoke. Exposure to combustion products may harm your health. Fire fighters should wear appropriate protection equipment. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.

6.2. Environmental precautions

No specific requirements.

6.3. Methods and material for containment and cleaning up

Use sand, sawdust, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations. To the extent possible cleaning is performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section on “Disposal considerations” in regard of handling of waste. See section on 'Exposure controls/personal protection' for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid static electricity. Protect electrical equipment in accordance with current standards. To divert static electricity during transmission, containers must be grounded and connected by wire with the receiving containers. Do not use spark-forming tools.
Smoking, storage of tobacco, consumption and storage of food or liquids are not allowed in the workrooms.
See section on 'Exposure controls/personal protection' for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Always store in containers of the same material as the original container. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Must be stored in a cool and well-ventilated area, away from possible sources of ignition.

Storage temperature

> 0 °C

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

OEL

propan-2-ol isopropyl alcohol isopropanol
Long-term exposure limit (8-hour TWA reference period): 400 ppm | 999 mg/m³
Short-term exposure limit (15-minute reference period): 500 ppm | 1250 mg/m³

ethanol ethyl alcohol
Long-term exposure limit (8-hour TWA reference period): 1000 ppm | 1920 mg/m³
Short-term exposure limit (15-minute reference period): - ppm | - mg/m³

DNEL / PNEC

DNEL (ethanol ethyl alcohol): 950 mg/m3
Exposure: Inhalation
Duration of Exposure: Long term – Systemic effects - Workers

DNEL (ethanol ethyl alcohol): 1900 mg/m3
Exposure: Inhalation
Duration of Exposure: Short term – Local effects - Workers

DNEL (ethanol ethyl alcohol): 343 mg/kg/bw/day
Exposure: Dermal
Duration of Exposure: Long term – Systemic effects - Workers

PNEC (ethanol ethyl alcohol): 0,96mg/l
Exposure: Freshwater

PNEC (ethanol ethyl alcohol): 0,79 mg/l
Exposure: Marine water

PNEC (ethanol ethyl alcohol): 2,75 mg/l
Exposure: Intermittent release

PNEC (ethanol ethyl alcohol): 580 mg/l
Exposure: Sewage Treatment Plant

PNEC (ethanol ethyl alcohol): 3,6 mg/kg dw
Exposure: Freshwater sediment

PNEC (ethanol ethyl alcohol): 2,9 mg/kg dw
Exposure: Marine water sediment

PNEC (ethanol ethyl alcohol): 0,63 mg/kg
Exposure: Soil

8.2. Exposure controls

Compliance with the accepted occupational exposure limits values should be controlled on a regular basis.

General recommendations

Observe general occupational hygiene standards.

Exposure scenarios

In the event exposure scenarios are appended to the safety data sheet, the operational conditions and risk management measures in these shall be complied with.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

Airborne gas and dust concentrations must be kept at a minimum and below current limit values (see above). Installation of an exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure emergency eyewash and -showers are clearly marked.

Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

Measures to avoid environmental exposure

No specific requirements.

Individual protection measures, such as personal protective equipment



Generally

Use only CE marked protective equipment.

Respiratory Equipment

In case of poor ventilation or exceedance of limit values
Recommended: A. Class 1 (low capacity). Brown

Skin protection

Wear appropriate protection clothing, e.g. coveralls in polypropylene approved type 6 and Category III.

Hand protection

Nitrile rubber
Breakthrough time: > 480 minutes (Class 6)

Eye protection

Wear safety glasses with side shields.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Form	Liquid
Colour	Colourless
Odour	Alcohol odor
Odour threshold (ppm)	No data available.
pH	8,5
Viscosity (40°C)	No data available.
Density (g/cm³)	0,88
Phase changes	
Melting point (°C)	No data available.
Boiling point (°C)	78
Vapour pressure	No data available.
Decomposition temperature (°C)	No data available.
Evaporation rate (n-butylacetate = 100)	No data available.
Data on fire and explosion hazards	
Flash point (°C)	21
Ignition (°C)	No data available.
Auto flammability (°C)	No data available.
Explosion limits (% v/v)	No data available.
Explosive properties	No data available.
Solubility	
Solubility in water	Soluble
n-octanol/water coefficient	No data available.

9.2. Other information

Solubility in fat (g/L)	No data available.

SECTION 10: Stability and reactivity

10.1. Reactivity
No data available

10.2. Chemical stability
The product is stable under the conditions, noted in the section “Handling and storage”.

10.3. Possibility of hazardous reactions
Nothing special

10.4. Conditions to avoid
Avoid static electricity.

10.5. Incompatible materials
Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products
The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity
Substance: propan-2-ol isopropyl alcohol isopropanol
Species: Rat
Test: LD50
Route of exposure: Oral
Result: 5045 mg/kg

Substance: propan-2-ol isopropyl alcohol isopropanol
Species: Rabbit
Test: LD50
Route of exposure: Dermal
Result: 12800 mg/kg

Substance: propan-2-ol isopropyl alcohol isopropanol
Species: Rat
Test: LC50
Route of exposure: Inhalation
Result: 16000 mg/l

Substance: ethanol ethyl alcohol
Species: Rat
Test: LD50
Route of exposure: Oral
Result: 7060 mg/kg

Substance: ethanol ethyl alcohol
Species: Rabbit
Test: LD lo
Route of exposure: Dermal
Result: 20 gram/kg

Substance: ethanol ethyl alcohol
Species: Rat
Test: LC50
Route of exposure: Inhalation
Result: 2000 ppm 10H

Skin corrosion/irritation
No data available.

Serious eye damage/irritation
Causes serious eye irritation.

Respiratory or skin sensitisation
No data available.

Germ cell mutagenicity
No data available.

Carcinogenicity
No data available.

Reproductive toxicity
No data available.

STOT-single exposure

No data available.

STOT-repeated exposure
No data available.

Aspiration hazard
No data available.

Long term effects
Causes serious eye irritation. The product releases vapors from organic solvents that can cause drowsiness and dizziness. At high concentrations, the fumes can cause headaches and intoxication. Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

SECTION 12: Ecological information

12.1. Toxicity
Substance: propan-2-ol isopropyl alcohol isopropanol
Species: Algae
Test: EC50
Duration: 24h
Result: 1000000 ug/l

Substance: propan-2-ol isopropyl alcohol isopropanol
Species: Fish
Test: LC50
Duration: 48h
Result: 1400000 ug/l

12.2. Persistence and degradability

Substance	Biodegradability	Test	Result

No data available.

12.3. Bioaccumulative potential

Substance	Potential bioaccumulation	LogPow	BCF
propan-2-ol isopropyl alcohol...	No	0,05	No data available

12.4. Mobility in soil
propan-2-ol isopropyl alcohol...: Log Koc= 0,117995 (High mobility potential.).

12.5. Results of PBT and vPvB assessment
This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

12.6. Other adverse effects
Nothing special

SECTION 13: Disposal considerations

13.1. Waste treatment methods
Product is covered by the regulations on hazardous waste.

Waste
EWC code
-

Specific labelling
Not applicable

Contaminated packing
Contaminated packaging must be disposed of similarly to the product.

SECTION 14: Transport information

14.1 – 14.4
This product is within scope of the regulations of transport of dangerous goods.

ADR/RID

14.1. UN number	1987
14.2. UN proper shipping name	-
14.3. Transport hazard class(es)	3
14.4. Packing group	III
Notes	-

Tunnel restriction code	-

IMDG

UN-no.	1987
Proper Shipping Name	Alcohols n.o.s. (ethanol and 2propanol)
Class	3
PG*	III
EmS	-
MP**	no
Hazardous constituent	-

IATA/ICAO

UN-no.	1987
Proper Shipping Name	Alcohols n.o.s. (ethanol and 2propanol)
Class	3
PG*	III

14.5. Environmental hazards

-

14.6. Special precautions for user

-

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available

(*) Packing group
(**) Marine pollutant

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

People under the age of 18 shall not be exposed to this product cf. Council Directive 94/33/EC of 22 June 1994 on the protection of young people at work.
Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

Demands for specific education

-

Additional information

Not applicable

Seveso

Seveso III Part 1: P5c

Biocidal reg. no.

Not applicable

Sources

Council Directive 94/33/EC of 22 June 1994 on the protection of young people at work.
The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677. The Stationery Office, 2002.
Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (CLP).
Regulation (EC) 1907/2006 (REACH).
The Control of Major Accident Hazards (COMAH) Regulations 2015.

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

H225 - Highly flammable liquid and vapour.
H319 - Causes serious eye irritation.

H336 - May cause drowsiness or dizziness.

The full text of identified uses as mentioned in section 1

PC8 = Biocidal Products (e.g. Disinfectants, pest control)
SU 4 = Manufacture of food products
ERC8a = Wide dispersive indoor use of processing aids in open systems

Additional label elements

Not applicable

Other

In accordance with Regulation (EC) No. 1272/2008 (CLP) the evaluation of the classification of the mixture is based on:
The classification of the mixture in regard of physical hazards has been based on experimental data.
The classification of the mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP)
It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.
The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.
A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The safety data sheet is validated by

mb

Date of last essential change
(First cipher in SDS version)

2020-03-05(1.0)

Date of last minor change
(Last cipher in SDS version)

2020-03-05