

SAFETY DATA SHEET

## Micro Oil

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Trade name

Micro Oil

Unique formula identifier (UFI)

UT66-N59T-P65P-8SNE

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Industrial purposes

Use descriptors (REACH)

Sector of use	Description
LCS "PW"	Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
LCS "C"	Consumer uses: Private households (= general public = consumers)
Product categories	Description
PC24	Lubricants, Greases and Release Products
Process Categories	Description
PROC11	Non industrial spraying
Environmental release categories	Description
ERC8a	Wide dispersive indoor use of processing aids in open systems

Uses advised against

No special

#### 1.3. Details of the supplier of the safety data sheet

Company and address

**Pureno A/S**

Rønnevangs Alle 8

3400 Hillerød

Danmark

+45 70 260 267

Contact person

Kenneth Christensen

E-mail

kc@pureno.dk

SDS date

2021-04-28

SDS Version

1.0

#### 1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service).

See section 4 "First aid measures".

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

Aerosol 1; H222, H229, Extremely flammable aerosol. Pressurised container: May burst if heated.

Asp. Tox. 1; H304, May be fatal if swallowed and enters airways.

### 2.2. Label elements

Hazard pictogram(s)



Signal word

Danger

Hazard statement(s)

Extremely flammable aerosol.

Pressurised container: May burst if heated.

Safety statement(s)

General

P102, Keep out of reach of children.

Prevention

P210, Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211, Do not spray on an open flame or other ignition source.

P251, Do not pierce or burn, even after use.

Response

-

Storage

P410+P412, Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.

Disposal

P501, Dispose of contents/container to an approved waste disposal plant.

Hazardous substances

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

### 2.3. Other hazards

Additional labelling

Not applicable

Additional warnings

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

In the event of leaks, high concentrations of gases can quickly form. They can be toxic, asphyxiating, or explosive.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
dimethoxymethan	CAS No.: 109-87-5 EC No.: 203-714-2 REACH: Index No.:	40-60%	Flam. Liq. 2, H225	

According to EC-Regulation 1907/2006 (REACH), annex II, as implemented by EC-Regulation 2015/830

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	CAS No.: 64742-48-9 EC No.: 919-857-5 REACH: Index No.:	10-15%	EUH066 Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336	
carbon dioxide	CAS No.: 124-38-9 EC No.: 204-696-9 REACH: Index No.:	5-10%	Press. Gas (Liq.) , H280	[1]

-----

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

#### Other information

[1] European occupational exposure limit

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

#### Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

#### Skin contact

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.

#### Eye contact

Upon irritation of the eye: Remove contact lenses and open eyes widely. Flush eyes with water or saline water(20-30°C) for at least 5 minutes. Seek medical assistance and continue flushing during transport.

#### Ingestion

IF SWALLOWED: Immediately call a POISON CENTER / doctor.

Do not induce vomiting! If vomiting occurs, keep head facing down so that vomit does not get into the lungs. Call a doctor or ambulance. Symptoms of chemical pneumonia can appear after several hours. People who have swallowed the product should therefore be kept under medical attention for at least 48 hours.

#### Burns

Rinse with water until pain stops then continue to rinse for 30 minutes.

### 4.2. Most important symptoms and effects, both acute and delayed

This product contains substances that can cause chemical pneumonia if swallowed. Symptoms of chemical pneumonia may appear after several hours.

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

### 4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned:

Get immediate medical advice/attention.

#### Information to medics

Bring this safety data sheet or the label from this product.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

### 5.2. Special hazards arising from the substance or mixture

Given that it does not present and hazard gas supplies shall be disrupted immediately. Removal of pressurized containers or attempting to cool with water shall be entrusted the fire brigade.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO<sub>2</sub>).

### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.

### 6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.

### 6.3. Methods and material for containment and cleaning up

Limit spillage and collect using granular absorbent or similar materials, and dispose of it in accordance with the regulations on dangerous waste.

Use sand, sawdust, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations.

To the extent possible cleaning is performed with normal cleaning agents. Avoid use of solvents.

### 6.4. Reference to other sections

See section 13 on "Disposal considerations" in regard of handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Avoid static electricity.

Protect electrical equipment in accordance with current standards. To divert static electricity during transmission, containers must be grounded and connected by wire with the receiving containers. Do not use spark-forming tools.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

### 7.2. Conditions for safe storage, including any incompatibilities

Must be stored in a cool and well-ventilated area, away from possible sources of ignition.

Pressurized gas packs (spray cans, aerosol cans) must be stored behind a wire mesh, which allows gases to escape and holds back packs flying around.

#### Recommended storage material

Always store in containers of the same material as the original container.

#### Storage temperature

> 0°C

#### Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

### 7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

—  
dimethoxymethan  
Long term exposure limit (8 hours) (ppm): 1000  
Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 3160  
Short term exposure limit (15 minutes) (ppm): 1250  
Short term exposure limit (15 minutes) (mg/m<sup>3</sup>): 3950

—  
carbon dioxide  
Long term exposure limit (8 hours) (ppm): 5000  
Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 9150  
Short term exposure limit (15 minutes) (ppm): 15000  
Short term exposure limit (15 minutes) (mg/m<sup>3</sup>): 27400

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002.  
EH40/2005 Workplace exposure limits (Fourth Edition 2020)

### DNEL

Product/substance	dimethoxymethan
DNEL	132 mg/m <sup>3</sup>
Route of exposure	Inhalation
Duration	Long term – Systemic effects - Workers

Product/substance	dimethoxymethan
DNEL	22mg/kg bw/day
Route of exposure	Dermal
Duration	Long term – Systemic effects - Workers

Product/substance	dimethoxymethan
DNEL	39 mg/m <sup>3</sup>
Route of exposure	Inhalation
Duration	Long term – Systemic effects - General population

Product/substance	dimethoxymethan
DNEL	5,7 mg/kg bw/day
Route of exposure	Dermal
Duration	Long term – Systemic effects - General population

Product/substance	dimethoxymethan
DNEL	9,6 mg/kg bw/day
Route of exposure	Oral
Duration	Long term – Systemic effects - General population

### PNEC

No data available

### 8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

#### General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

#### Exposure scenarios

There are no exposure scenarios implemented for this product.

#### Exposure limits

According to EC-Regulation 1907/2006 (REACH), annex II, as implemented by EC-Regulation 2015/830

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

### Appropriate technical measures

Adequate ventilation must be ensured for all gases. Where natural ventilation is not possible (cellar rooms), artificial ventilation must be installed. It is advantageous to store it in a lattice shed outdoors, as ventilation is no longer necessary in this case.

### Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

### Measures to avoid environmental exposure

No specific requirements

### Individual protection measures, such as personal protective equipment

#### Generally

Use only CE marked protective equipment.

#### Respiratory Equipment

Work situation	Type	Class	Colour	Standards
When developing vapour, use respiratory protection with approved filter	Normally, personal respiratory equipment is not necessary			

#### Skin protection

Work situation	Recommended	Type/Category	Standards
	Dedicated work clothing should be worn	-	-



#### Hand protection

Work situation	Material	Glove thickness (mm)	Breakthrough time (min.)	Standards
	Nitrile	0.3	> 60	EN374-2, EN374-3, EN388



#### Eye protection

Work situation	Type	Standards
	In the likelihood of direct or incidental exposure, use eye protection.	EN166



## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

#### Form

Aerosol

#### Colour

Colourless

#### Odour

Faint

#### Odour threshold (ppm)

Testing not relevant or not possible due to nature of the product.

## pH

Testing not relevant or not possible due to nature of the product.

## Density (g/cm<sup>3</sup>)

0.80

## Viscosity

Testing not relevant or not possible due to nature of the product.

## Phase changes

### Melting point (°C)

Testing not relevant or not possible due to nature of the product.

### Boiling point (°C)

Testing not relevant or not possible due to nature of the product.

### Vapour pressure

Testing not relevant or not possible due to nature of the product.

### Vapour density

Testing not relevant or not possible due to nature of the product.

### Decomposition temperature (°C)

Testing not relevant or not possible due to nature of the product.

### Evaporation rate (n-butylacetate = 100)

## Data on fire and explosion hazards

### Flash point (°C)

-30.00 °C

### Ignition (°C)

Testing not relevant or not possible due to nature of the product.

### Auto flammability (°C)

Testing not relevant or not possible due to nature of the product.

### Explosion limits (% v/v)

Testing not relevant or not possible due to nature of the product.

### Explosive properties

Testing not relevant or not possible due to nature of the product.

### Oxidizing properties

Testing not relevant or not possible due to nature of the product.

## Solubility

### Solubility in water

Testing not relevant or not possible due to nature of the product.

### n-octanol/water coefficient

Testing not relevant or not possible due to nature of the product.

### Solubility in fat (g/L)

Testing not relevant or not possible due to nature of the product.

## 9.2. Other information

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No data available

### 10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

### 10.3. Possibility of hazardous reactions

No special

### 10.4. Conditions to avoid

Avoid static electricity.

Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure.

### 10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

### 10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity

Product/substance	dimethoxymethan
Test method	
Species	Rat
Route of exposure	Oral
Test	LD50
Result	6423 mg/kg ·
Other information	

Product/substance	dimethoxymethan
Test method	
Species	Mouse
Route of exposure	Oral
Test	LD50
Result	6950 mg/kg ·
Other information	

Product/substance	dimethoxymethan
Test method	
Species	Rabbit
Route of exposure	Dermal
Test	LD50
Result	>500 mg/kg ·
Other information	

Product/substance	carbon dioxide
Test method	
Species	Rat
Route of exposure	Inhalation
Test	LC50
Result	470000 ppm 0,5 h ·
Other information	

#### Skin corrosion/irritation

Based on available data, the classification criteria are not met.

#### Serious eye damage/irritation

Based on available data, the classification criteria are not met.

#### Respiratory sensitisation

Based on available data, the classification criteria are not met.

#### Skin sensitisation

Based on available data, the classification criteria are not met.

#### Germ cell mutagenicity

Based on available data, the classification criteria are not met.

#### Carcinogenicity

Based on available data, the classification criteria are not met.

#### Reproductive toxicity

Based on available data, the classification criteria are not met.

#### STOT-single exposure

Based on available data, the classification criteria are not met.



## STOT-repeated exposure

Based on available data, the classification criteria are not met.

## Aspiration hazard

May be fatal if swallowed and enters airways.

## Long term effects

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

## Other information

No special

## SECTION 12: Ecological information

### 12.1. Toxicity

Product/substance	dimethoxymethan
Test method	
Species	Fish
Compartment	
Duration	96 hours
Test	LC50
Result	>1000 mg/l ·
Other information	

Product/substance	dimethoxymethan
Test method	
Species	Daphnia
Compartment	
Duration	48 hours
Test	LC50
Result	>1200mg/l ·
Other information	

### 12.2. Persistence and degradability

No data available

### 12.3. Bioaccumulative potential

Product/substance	carbon dioxide
Test method	
Potential bioaccumulation	No
LogPow	0,8300
BCF	No data available
Other information	

### 12.4. Mobility in soil

No data available

### 12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

### 12.6. Other adverse effects

No special

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Product is covered by the regulations on hazardous waste.

HP 3 - Flammable

#### EWC code

16 05 04\* Gases in pressure containers (including halons) containing dangerous substances

#### Specific labelling

Not applicable

#### Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

## SECTION 14: Transport information

### 14.1 - 14.4

This product is within scope of the regulations of transport of dangerous goods.

#### ADR/RID

UN- or ID number	UN proper shipping name	Labels	PG	Tunnel restriction code
1950	AEROSOLS	2.1		2 (D)

#### IMDG

UN- or ID number	UN proper shipping name	Labels	PG	EmS
1950	AEROSOLS	2.1		F-D, S-U

#### IATA

UN- or ID number	UN proper shipping name	Labels	PG
1950	AEROSOLS	2.1	

"MARINE POLLUTANT"

No

### 14.5. Environmental hazards

Not applicable

### 14.6. Special precautions for user

Not applicable

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Restrictions for application

People under the age of 18 shall not be exposed to this product.

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

#### Demands for specific education

No specific requirements

#### SEVESO - Categories / dangerous substances

P3b - FLAMMABLE AEROSOLS, Qualifying quantity (lower-tier): 5.000 tonnes (net) / (upper-tier): 50.000 tonnes (net)

#### Additional information

Tactile warning.

#### Sources

The Health and Safety at Work etc. Act 1974 Regulations 2013.

The Aerosol Dispensers Regulations 2009 No. 2824, amended in 2014 (No. 1130) and in 2018 (No. 29)

Control of Major Accident Hazards (COMAH) Regulations 2015.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (CLP).

Regulation (EC) 1907/2006 (REACH).

#### 15.2. Chemical safety assessment

No

### SECTION 16: Other information

#### Full text of H-phrases as mentioned in section 3

H225, Highly flammable liquid and vapour.

EUH066, Repeated exposure may cause skin dryness or cracking.

H226, Flammable liquid and vapour.

H304, May be fatal if swallowed and enters airways.

H336, May cause drowsiness or dizziness.

H280, Contains gas under pressure; may explode if heated.

#### The full text of identified uses as mentioned in section 1

LCS "PW" = Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

LCS "C" = Consumer uses: Private households (= general public = consumers)

PROC11 = Non industrial spraying

PC24 = Lubricants, Greases and Release Products

ERC8a = Wide dispersive indoor use of processing aids in open systems

#### Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CE = Conformité Européenne

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial chemical Substances

ES = Exposure Scenario

EUH statement = CLP-specific Hazard statement

EWC = European Waste Catalogue

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IARC = International Agency for Research on Cancer (IARC)

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

OECD = Organisation for Economic Co-operation and Development  
PBT = Persistent, Bioaccumulative and Toxic  
PNEC = Predicted No Effect Concentration  
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail  
RRN = REACH Registration Number  
SCL = A specific concentration limit.  
SVHC = Substances of Very High Concern  
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure  
STOT-SE = Specific Target Organ Toxicity - Single Exposure  
TWA = Time weighted average  
UN = United Nations  
UVCB = Complex hydrocarbon substance  
VOC = Volatile Organic Compound  
vPvB = Very Persistent and Very Bioaccumulative

#### Additional information

In accordance with Regulation (EC) No. 1272/2008 (CLP) the evaluation of the classification of the substance/mixture is based on:

The classification of the substance/mixture in regard of physical hazards has been based on experimental data.

#### The safety data sheet is validated by

LT

#### Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en