

SAFETY DATA SHEET

Welding Spray

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Trade name

Welding Spray

Unique formula identifier (UFI)

P7XX-HXMC-D4E0-V21T

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Industrial purposes

Uses advised against

No special

1.3. Details of the supplier of the safety data sheet

Company and address

Pureno A/S

Rønnevangs Alle 8

3400 Hillerød

Danmark

+45 70 260 267

Contact person

Kenneth Christensen

E-mail

kc@pureno.dk

SDS date

2021-06-07

SDS Version

2.0

Date of previous version

2021-02-04 (1.0)

1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service).

See section 4 "First aid measures".

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture**

Aerosol 3; H229, Pressurised container: May burst if heated.

Eye Irrit. 2; H319, Causes serious eye irritation.

Aquatic Chronic 3; H412, Harmful to aquatic life with long lasting effects.

2.2. Label elements

Hazard pictogram(s)



Signal word

Warning

Hazard statement(s)

Pressurised container: May burst if heated.
 Causes serious eye irritation.
 Harmful to aquatic life with long lasting effects.

Safety statement(s)

General

P101, If medical advice is needed, have product container or label at hand.
 P102, Keep out of reach of children.

Prevention

P210, Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P251, Do not pierce or burn, even after use.

Response

P305+P351+P338, IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P337+P313, If eye irritation persists: Get medical advice/attention.

Storage

P410+P412, Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.

Disposal

P501, Dispose of contents/container to an approved waste disposal plant.

Hazardous substances

No special

2.3. Other hazards

Additional labelling

Not applicable

Additional warnings

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

SECTION 3: Composition/information on ingredients

▼ 3.2 Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
ethanol	CAS No.: 64-17-5 EC No.: 200-578-6 REACH: 01-2120063206-63-XXXX Index No.: 603-002-00-5	10-15%	Flam. Liq. 2, H225 Eye Irrit. 2, H319 (SCL: 50.00 %)	
carbon dioxide	CAS No.: 124-38-9 EC No.: 204-696-9 REACH: Index No.:	5-10%	Press. Gas (Liq.) , H280	[1]
amider, C8-18- og C18-umættede, N,N-bis-(hydroxyethyl)	CAS No.: 68155-07-7 EC No.: 931-329-6 REACH: Index No.:	1-3%	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 2, H411	

According to EC-Regulation 1907/2006 (REACH), annex II, as implemented by EC-Regulation 2015/830

2,2',2''-nitrilotriethanol	CAS No.: 102-71-6 EC No.: 203-049-8 REACH: Index No.:	1-3%	Skin Irrit. 2, H315 Eye Irrit. 2, H319
Propan-2-ol	CAS No.: 67-63-0 EC No.: 200-661-7 REACH: Index No.: 603-117-00-0	1-3%	Flam. Liq. 2, H225 STOT SE 3, H336 Eye Irrit. 2, H319

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

[1] European occupational exposure limit

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

Upon irritation: rinse with water. In the event of continued irritation, seek medical assistance.

Eye contact

Upon irritation of the eye: Remove contact lenses. Flush eyes immediately with plenty of water or isotonic water (20-30°C) for at least 5 minutes and continue until irritation stops. Make sure to flush under upper and lower eyelids. If irritation continues, contact a doctor. Continue flushing during transport.

Ingestion

Provide plenty of water for the person to drink and stay with him/her. In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the victim lean forward with head down to avoid inhalation of- or choking on vomited material.

Burns

Not applicable

4.2. Most important symptoms and effects, both acute and delayed

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned:

Get immediate medical advice/attention.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Not applicable

▼ 5.2. Special hazards arising from the substance or mixture

Given that it does not present and hazard gas supplies shall be disrupted immediately. Removal of pressurized containers or attempting to cool with water shall be entrusted the fire brigade.

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO₂).

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

No specific requirements

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities.

6.3. Methods and material for containment and cleaning up

Limit spillage and collect using granular absorbent or similar materials, and dispose of it in accordance with the regulations on dangerous waste.

Use sand, sawdust, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations.

To the extent possible cleaning is performed with normal cleaning agents. Avoid use of solvents.

▼ 6.4. Reference to other sections

See section 13 on "Disposal considerations" in regard of handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

▼ 7.1. Precautions for safe handling

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

▼ 7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers and store protected from moisture and light. Containers should be dated when opened and tested periodically for the presence of peroxides. Do not exceed storage time limits.

Recommended storage material

Always store in containers of the same material as the original container.

Storage temperature

No specific requirements

Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

—
ethanol

Long term exposure limit (8 hours) (ppm): 1000

According to EC-Regulation 1907/2006 (REACH), annex II, as implemented by EC-Regulation 2015/830

Long term exposure limit (8 hours) (mg/m³): 1920

—
carbon dioxide

Long term exposure limit (8 hours) (ppm): 5000

Long term exposure limit (8 hours) (mg/m³): 9150

Short term exposure limit (15 minutes) (ppm): 15000

Short term exposure limit (15 minutes) (mg/m³): 27400

—
Propan-2-ol

Long term exposure limit (8 hours) (ppm): 400

Long term exposure limit (8 hours) (mg/m³): 999

Short term exposure limit (15 minutes) (ppm): 500

Short term exposure limit (15 minutes) (mg/m³): 1250

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002.
EH40/2005 Workplace exposure limits (Fourth Edition 2020)

▼ DNEL

Product/substance	ethanol
DNEL	950 mg/m ³
Route of exposure	Inhalation
Duration	Long term – Systemic effects - Workers

Product/substance	ethanol
DNEL	1900 mg/m ³
Route of exposure	Inhalation
Duration	Short term – Local effects - Workers

Product/substance	ethanol
DNEL	343 mg/kg legemsvægt pr. dag
Route of exposure	Dermal
Duration	Long term – Systemic effects - Workers

Product/substance	ethanol
DNEL	114 mg/m ³
Route of exposure	Inhalation
Duration	Long term – Systemic effects - General population

Product/substance	ethanol
DNEL	950 mg/m ³
Route of exposure	Inhalation
Duration	Short term – Local effects - General population

Product/substance	ethanol
DNEL	206 mg/kg legemsvægt pr. dag
Route of exposure	Dermal
Duration	Long term – Systemic effects - General population

Product/substance	ethanol
DNEL	87 mg/kg legemsvægt pr. dag
Route of exposure	Oral
Duration	Long term – Systemic effects - General population

Product/substance	amider, C8-18- og C18-umættede, N,N-bis-(hydroxyethyl)
-------------------	--

According to EC-Regulation 1907/2006 (REACH), annex II, as implemented by EC-Regulation 2015/830

DNEL	4,16 mg/kg bw/day
Route of exposure	Dermal
Duration	Long term – Systemic effects - Workers
Product/substance	amider, C8-18- og C18-umættede, N,N-bis-(hydroxyethyl)
DNEL	73,4 mg/m ³
Route of exposure	Inhalation
Duration	Long term – Systemic effects - Workers
Product/substance	amider, C8-18- og C18-umættede, N,N-bis-(hydroxyethyl)
DNEL	0,09 mg/cm ²
Route of exposure	Dermal
Duration	Long term – Local effects - Workers
Product/substance	amider, C8-18- og C18-umættede, N,N-bis-(hydroxyethyl)
DNEL	2,5 mg/kg bw/day
Route of exposure	Dermal
Duration	Long term – Systemic effects - General population
Product/substance	amider, C8-18- og C18-umættede, N,N-bis-(hydroxyethyl)
DNEL	21,73 mg/m ³
Route of exposure	Inhalation
Duration	Long term – Systemic effects - General population
Product/substance	amider, C8-18- og C18-umættede, N,N-bis-(hydroxyethyl)
DNEL	6,25 mg/kg bw/day
Route of exposure	Oral
Duration	Long term – Systemic effects - General population
Product/substance	amider, C8-18- og C18-umættede, N,N-bis-(hydroxyethyl)
DNEL	0,056 mg/cm ²
Route of exposure	Dermal
Duration	Long term – Local effects - General population
Product/substance	Propan-2-ol
DNEL	888 mg/kg bw/dag
Route of exposure	Dermal
Duration	Long term – Systemic effects - Workers
Product/substance	Propan-2-ol
DNEL	500 mg/m ³
Route of exposure	Inhalation
Duration	Long term – Systemic effects - Workers
Product/substance	Propan-2-ol
DNEL	319mg/kg bw/dag
Route of exposure	Dermal
Duration	Long term – Systemic effects - General population
Product/substance	Propan-2-ol
DNEL	89mg/m ³
Route of exposure	Inhalation

According to EC-Regulation 1907/2006 (REACH), annex II, as implemented by EC-Regulation 2015/830

Duration	Long term – Systemic effects - General population
----------	---

Product/substance	Propan-2-ol
DNEL	26mg/kg bw/dag
Route of exposure	Oral
Duration	Long term – Systemic effects - General population

▼ PNEC

Product/substance	ethanol
PNEC	0,96 mg/l
Route of exposure	Freshwater
Duration of Exposure	

Product/substance	ethanol
PNEC	0,79 mg/l
Route of exposure	Marine water
Duration of Exposure	

Product/substance	ethanol
PNEC	2,75 mg/l
Route of exposure	Intermittent release
Duration of Exposure	

Product/substance	ethanol
PNEC	580 mg/l
Route of exposure	Sewage treatment plant
Duration of Exposure	

Product/substance	ethanol
PNEC	3,6 mg/kg
Route of exposure	Freshwater sediment
Duration of Exposure	

Product/substance	ethanol
PNEC	2,9 mg/kg
Route of exposure	Marine water sediment
Duration of Exposure	

Product/substance	ethanol
PNEC	0,63 mg/kg
Route of exposure	Soil
Duration of Exposure	

Product/substance	amider, C8-18- og C18-umættede, N,N-bis-(hydroxyethyl)
PNEC	0,0024 mg/l
Route of exposure	Freshwater
Duration of Exposure	

Product/substance	amider, C8-18- og C18-umættede, N,N-bis-(hydroxyethyl)
PNEC	0,00024 mg/l
Route of exposure	Marine water

According to EC-Regulation 1907/2006 (REACH), annex II, as implemented by EC-Regulation 2015/830

Duration of Exposure

Product/substance	amider, C8-18- og C18-umættede, N,N-bis-(hydroxyethyl)
PNEC	0,024 mg/l
Route of exposure	Intermittent release
Duration of Exposure	

Product/substance	amider, C8-18- og C18-umættede, N,N-bis-(hydroxyethyl)
PNEC	0,83 mg/l
Route of exposure	Sewage treatment plant
Duration of Exposure	

Product/substance	amider, C8-18- og C18-umættede, N,N-bis-(hydroxyethyl)
PNEC	0,00648 mg/kg tør vægt
Route of exposure	Soil
Duration of Exposure	

Product/substance	amider, C8-18- og C18-umættede, N,N-bis-(hydroxyethyl)
PNEC	0,0145 mg/kg
Route of exposure	Freshwater sediment
Duration of Exposure	

Product/substance	Propan-2-ol
PNEC	552mg/kg
Route of exposure	Marine water sediment
Duration of Exposure	

Product/substance	Propan-2-ol
PNEC	140,9 mg/l
Route of exposure	Freshwater
Duration of Exposure	

Product/substance	Propan-2-ol
PNEC	28 mg/kg
Route of exposure	Soil
Duration of Exposure	

Product/substance	Propan-2-ol
PNEC	140,9 mg/l
Route of exposure	Marine water
Duration of Exposure	

Product/substance	Propan-2-ol
PNEC	140,9 mg/l
Route of exposure	Intermittent release
Duration of Exposure	

Product/substance	Propan-2-ol
PNEC	251 mg/l
Route of exposure	Sewage treatment plant
Duration of Exposure	

According to EC-Regulation 1907/2006 (REACH), annex II, as implemented by EC-Regulation 2015/830

Product/substance	Propan-2-ol
PNEC	552 mg/kg
Route of exposure	Freshwater sediment
Duration of Exposure	

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

Apply standard precautions during use of the product. Avoid inhalation of gas or dust.

Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

Measures to avoid environmental exposure

No specific requirements

Individual protection measures, such as personal protective equipment

Generally

Use only CE marked protective equipment.

Respiratory Equipment

Work situation	Type	Class	Colour	Standards
When developing vapour, use respiratory protection with approved filter	Normally, personal respiratory equipment is not necessary			

Skin protection

Work situation	Recommended	Type/Category	Standards
	Dedicated work clothing should be worn	-	-



Hand protection

Work situation	Material	Glove thickness (mm)	Breakthrough time (min.)	Standards
	Nitrile	0.3	> 60	EN374-2, EN374-3, EN388



Eye protection

Work situation	Type	Standards
	No special when used as intended.	-

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Form

Aerosol

Colour

Colourless

Odour

None

Odour threshold (ppm)

Testing not relevant or not possible due to nature of the product.

pH

Testing not relevant or not possible due to nature of the product.

Density (g/cm³)

Testing not relevant or not possible due to nature of the product.

Viscosity

Testing not relevant or not possible due to nature of the product.

Phase changes

Melting point (°C)

Testing not relevant or not possible due to nature of the product.

Boiling point (°C)

Testing not relevant or not possible due to nature of the product.

Vapour pressure

Testing not relevant or not possible due to nature of the product.

Vapour density

Testing not relevant or not possible due to nature of the product.

Decomposition temperature (°C)

Testing not relevant or not possible due to nature of the product.

▼ Evaporation rate (n-butylacetate = 100)

Data on fire and explosion hazards

▼ Flash point (°C)

24.00 °C

Ignition (°C)

Testing not relevant or not possible due to nature of the product.

Auto flammability (°C)

Testing not relevant or not possible due to nature of the product.

Explosion limits (% v/v)

Testing not relevant or not possible due to nature of the product.

Explosive properties

Testing not relevant or not possible due to nature of the product.

Oxidizing properties

Testing not relevant or not possible due to nature of the product.

Solubility

Solubility in water

Soluble

n-octanol/water coefficient

Testing not relevant or not possible due to nature of the product.

Solubility in fat (g/L)

Testing not relevant or not possible due to nature of the product.

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available

▼ 10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

No special

10.4. Conditions to avoid

No special

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

▼ Acute toxicity

Product/substance	ethanol
Test method	
Species	Rat
Route of exposure	Oral
Test	LD50
Result	10470 mg/kg ·
Other information	

Product/substance	ethanol
Test method	
Species	Rabbit
Route of exposure	Dermal
Test	LD50
Result	>17100 mg/kg ·
Other information	

Product/substance	ethanol
Test method	
Species	Rat
Route of exposure	Inhalation
Test	LC50
Result	124,7 mg/l ·
Other information	

Product/substance	carbon dioxide
Test method	
Species	Rat
Route of exposure	Inhalation
Test	LC50
Result	470000 ppm 0,5 h ·
Other information	

Product/substance	amider, C8-18- og C18-umættede, N,N-bis-(hydroxyethyl)
Test method	
Species	Rat
Route of exposure	Oral
Test	LD50
Result	>5000mg/kg ·
Other information	

According to EC-Regulation 1907/2006 (REACH), annex II, as implemented by EC-Regulation 2015/830

Product/substance	amider, C8-18- og C18-umættede, N,N-bis-(hydroxyethyl)
Test method	
Species	Rat
Route of exposure	Oral
Test	LC50
Result	>2000 mg/kg ·
Other information	

Product/substance	amider, C8-18- og C18-umættede, N,N-bis-(hydroxyethyl)
Test method	
Species	Rabbit
Route of exposure	Dermal
Test	LC50
Result	>2000mg/kg ·
Other information	

Product/substance	amider, C8-18- og C18-umættede, N,N-bis-(hydroxyethyl)
Test method	
Species	Rat
Route of exposure	Dermal
Test	NOAEL
Result	>1000 mg/kg ·
Other information	

Product/substance	2,2',2"-nitrilotriethanol
Test method	
Species	Guinea pig
Route of exposure	Oral
Test	LD50
Result	2200 mg/kg ·
Other information	

Product/substance	2,2',2"-nitrilotriethanol
Test method	
Species	Mouse
Route of exposure	Oral
Test	LD50
Result	5846 mg/kg ·
Other information	

Product/substance	2,2',2"-nitrilotriethanol
Test method	
Species	Rabbit
Route of exposure	Oral
Test	LD50
Result	2200 mg/kg ·
Other information	

Product/substance	Propan-2-ol
Test method	
Species	Rabbit
Route of exposure	Dermal

According to EC-Regulation 1907/2006 (REACH), annex II, as implemented by EC-Regulation 2015/830

Test	LD50
Result	>2000 mg/kg ·
Other information	

Product/substance	Propan-2-ol
Test method	
Species	Rat
Route of exposure	Oral
Test	LD50
Result	5840 mg/kg ·
Other information	

Product/substance	Propan-2-ol
Test method	
Species	Rat
Route of exposure	Inhalation
Test	LC50
Result	66,1 mg/l 4 h ·
Other information	

Product/substance	Propan-2-ol
Test method	
Species	Rat
Route of exposure	Inhalation
Test	LC50
Result	47,5 mg/l 8 h ·
Other information	

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Long term effects

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

Other information

ethanol has been classified by IARC as a group 1 carcinogen.

According to EC-Regulation 1907/2006 (REACH), annex II, as implemented by EC-Regulation 2015/830

2,2',2"-nitrioltriethanol has been classified by IARC as a group 3 carcinogen.
 Propan-2-ol has been classified by IARC as a group 3 carcinogen.

SECTION 12: Ecological information

▼ 12.1. Toxicity

Product/substance	ethanol
Test method	
Species	Fish
Compartment	
Duration	48 hours
Test	LC50
Result	8150 mg/l ·
Other information	

Product/substance	ethanol
Test method	
Species	Fish
Compartment	
Duration	96 hours
Test	LC50
Result	1100 mg/l ·
Other information	

Product/substance	ethanol
Test method	
Species	Daphnia
Compartment	
Duration	48 hours
Test	EC50
Result	9268-14221 mg/l ·
Other information	

Product/substance	ethanol
Test method	
Species	Algae
Compartment	
Duration	7 days
Test	EC0
Result	5000 mg/l ·
Other information	

Product/substance	ethanol
Test method	
Species	Crustacean
Compartment	
Duration	16 hours
Test	EC0
Result	6500 mg/l ·
Other information	

Product/substance	amider, C8-18- og C18-umættede, N,N-bis-(hydroxyethyl)
-------------------	--

According to EC-Regulation 1907/2006 (REACH), annex II, as implemented by EC-Regulation 2015/830

Test method
 Species Fish
 Compartment
 Duration 96 hours
 Test LC50
 Result 1-5mg/l ·
 Other information

Product/substance amider, C8-18- og C18-umættede, N,N-bis-(hydroxyethyl)
 Test method
 Species Daphnia
 Compartment
 Duration 72 hours
 Test EC50
 Result 5-15 mg/l ·
 Other information

Product/substance amider, C8-18- og C18-umættede, N,N-bis-(hydroxyethyl)
 Test method
 Species Algae
 Compartment
 Duration 48 hours
 Test EC50
 Result 1-5 mg/l ·
 Other information

Product/substance 2,2',2''-nitrilotriethanol
 Test method
 Species Fish
 Compartment
 Duration No data available.
 Test LC50
 Result 1800-11800 mg/l ·
 Other information

Product/substance 2,2',2''-nitrilotriethanol
 Test method
 Species Daphnia
 Compartment
 Duration No data available.
 Test LC50
 Result 1390-2038 mg/l ·
 Other information

Product/substance 2,2',2''-nitrilotriethanol
 Test method
 Species Algae
 Compartment
 Duration No data available.
 Test EC50
 Result 470-750 mg/l ·
 Other information

According to EC-Regulation 1907/2006 (REACH), annex II, as implemented by EC-Regulation 2015/830

Product/substance	2,2',2"-nitrilotriethanol
Test method	
Species	Crustacean
Compartment	
Duration	No data available.
Test	IC50
Result	>5000 mg/l ·
Other information	

Product/substance	Propan-2-ol
Test method	
Species	Algae
Compartment	
Duration	8 days
Test	NOEC
Result	>1800 mg/l ·
Other information	

Product/substance	Propan-2-ol
Test method	
Species	Fish
Compartment	
Duration	96 hours
Test	LC50
Result	8970-9280 mg/l ·
Other information	

Product/substance	Propan-2-ol
Test method	
Species	Daphnia
Compartment	
Duration	24 hours
Test	EC50
Result	9714 mg/l ·
Other information	

Product/substance	Propan-2-ol
Test method	
Species	Crustacean
Compartment	
Duration	18 hours
Test	EC10
Result	5175 mg/l ·
Other information	

Product/substance	Propan-2-ol
Test method	
Species	Crustacean
Compartment	
Duration	No data available.
Test	EC50
Result	>1000mg/l ·

Other information

▼ 12.2. Persistence and degradability

Product/substance	ethanol
Biodegradable	Yes
Test method	
Result	

Product/substance	2,2',2''-nitrilotriethanol
Biodegradable	Yes
Test method	
Result	

Product/substance	Propan-2-ol
Biodegradable	Yes
Test method	OECD 301 E
Result	95%

▼ 12.3. Bioaccumulative potential

Product/substance	ethanol
Test method	
Potential bioaccumulation	No
LogPow	No data available
BCF	No data available
Other information	

Product/substance	carbon dioxide
Test method	
Potential bioaccumulation	No
LogPow	0,8300
BCF	No data available
Other information	

Product/substance	Propan-2-ol
Test method	
Potential bioaccumulation	No
LogPow	No data available
BCF	No data available
Other information	

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

12.6. Other adverse effects

This product contains substances that are toxic to the environment. May result in adverse effects to aquatic organisms.

This product contains substances, which may cause adverse long-term effects to the aquatic environment.

SECTION 13: Disposal considerations

▼ 13.1. Waste treatment methods

To the extent the material has not been subject to regular tests of peroxide formation the waste shall be treated as explosive waste.

Product is covered by the regulations on hazardous waste.

Avoid discharge to lakes, streams, sewers, etc.

Dispose of contents/container to an approved waste disposal plant.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

EWC code

16 05 04* Gases in pressure containers (including halons) containing dangerous substances

Specific labelling

Not applicable

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

14.1 - 14.4

This product is within scope of the regulations of transport of dangerous goods.

▼ ADR/RID

UN- or ID number	UN proper shipping name	Labels	PG	Tunnel restriction code
1950	AEROSOLS	2.2		3 (E)

▼ IMDG

UN- or ID number	UN proper shipping name	Labels	PG	EmS
1950	AEROSOLS	2.2		F-D, S-U

"MARINE POLLUTANT"

No

▼ IATA

UN- or ID number	UN proper shipping name	Labels	PG
1950	AEROSOLS	2.2	

14.5. Environmental hazards

Not applicable

14.6. Special precautions for user

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

Demands for specific education

No specific requirements

SEVESO - Categories / dangerous substances

Not applicable

Additional information

Not applicable

▼ Sources

The Health and Safety at Work etc. Act 1974 Regulations 2013.

The Aerosol Dispensers Regulations 2009 No. 2824, amended in 2014 (No. 1130) and in 2018 (No. 29) Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (CLP).

Regulation (EC) 1907/2006 (REACH).

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

H319, Causes serious eye irritation.

H225, Highly flammable liquid and vapour.

H280, Contains gas under pressure; may explode if heated.

H315, Causes skin irritation.

H318, Causes serious eye damage.

H411, Toxic to aquatic life with long lasting effects.

H336, May cause drowsiness or dizziness.

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CE = Conformité Européenne

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial chemical Substances

ES = Exposure Scenario

EUH statement = CLP-specific Hazard statement

EWC = European Waste Catalogue

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IARC = International Agency for Research on Cancer (IARC)

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

OECD = Organisation for Economic Co-operation and Development

PBT = Persistent, Bioaccumulative and Toxic

PNEC = Predicted No Effect Concentration

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RRN = REACH Registration Number
SCL = A specific concentration limit.
SVHC = Substances of Very High Concern
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
STOT-SE = Specific Target Organ Toxicity - Single Exposure
TWA = Time weighted average
UN = United Nations
UVCB = Complex hydrocarbon substance
VOC = Volatile Organic Compound
vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the substance/mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP)

The safety data sheet is validated by

LT

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en