

SAFETY DATA SHEET

Multifoam

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

Multifoam

Unique formula identifier (UFI)

PNJT-CGT3-X207-5TRJ

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Cleaning product

Use descriptors (REACH)

Sectors of use	Description
LCS "PW"	Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
LCS "C"	Consumer uses: Private households (= general public = consumers)
Product category	Description
PC 35	Washing and Cleaning Products (including solvent based products)
Process category	Description
PROC 11	Non industrial spraying
Environmental release category	Description
ERC 8a	Wide dispersive indoor use of processing aids in open systems

Uses advised against

None known.

1.3. Details of the supplier of the safety data sheet

Company and address

Pureno A/S

Rønnevangs Alle 8

3400 Hillerød

Denmark

+45 70 260 267

Contact person

Kenneth Christensen

E-mail

kc@pureno.dk

Revision

4/19/2023

SDS Version

1.0

1.4. Emergency telephone number

Contact the poison hotline: +45 82 12 12 12 (24 hour service)

See section 4 "First aid measures".

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Aerosol 1; H222, H229, Extremely flammable aerosol. Pressurised container: May burst if heated.

This product is an aerosol dispenser where the propellant is separated from the product upon spraying. As a result, the concentrations of the propellants are not considered for the classification of the mixture in regard of health and environment.

2.2. Label elements

According to EC-Regulation 2015/830

Hazard pictogram(s)



Signal word

Danger

Hazard statement(s)

Extremely flammable aerosol. Pressurised container: May burst if heated. (H222, H229)

Precautionary statements

General

Keep out of reach of children. (P102)

Prevention

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. (P210)

Do not spray on an open flame or other ignition source. (P211)

Do not pierce or burn, even after use. (P251)

Response

-

Storage

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F. (P410+P412)

Disposal

-

Hazardous substances

Sulfuric acid, mono-C12-14-alkyl esters, sodium salts

(R)-p-mentha-1,8-diene;dipentene;(±)-1-methyl-4-(1-methylvinyl)cyclohexene;(S)-p-mentha-1,8-diene;trans-1-methyl-4-(1-methylvinyl)cyclohexene;d-limonene;limonene;limonene

Additional labelling

UFI: PNJT-CGT3-X207-5TRJ

2.3. Other hazards

Additional warnings

In the event of leaks, high concentrations of gases can quickly form. They can be toxic, asphyxiating, or explosive. This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable. This product is a mixture.

3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
Sulfuric acid, mono-C12-14-alkyl esters, sodium salts	CAS No.: 85586-07-8 EC No.: 287-809-4 REACH: 01-2119489463-28-XXXX Index No.:	10-15%	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 (SCL: 20.00 %) Aquatic Chronic 3, H412	
Butane	CAS No.: 106-97-8 EC No.: 203-448-7 REACH: Index No.: 601-004-00-0	5-10%	Flam. Gas 1A, H220	[16]
2-butoxyethanol	CAS No.: 111-76-2 EC No.: 203-905-0 REACH: Index No.: 603-014-00-0	5-10%	Acute Tox. 4, H302 (ATE: 1200.00 mg/kg) Acute Tox. 4, H312 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Acute Tox. 4, H332	[1]
Propane	CAS No.: 74-98-6 EC No.: 200-827-9 REACH: Index No.: 601-003-00-5	5-10%	Flam. Gas 1A, H220	[16]

According to EC-Regulation 2015/830

(R)-p-mentha-1,8-diene;dipentene;(±)-1-methyl-4-(1-methylvinyl)cyclohexene;(S)-p-mentha-1,8-diene;trans-1-methyl-4-(1-methylvinyl)cyclohexene;d-limonene;limonene;l-limonene	CAS No.: 5989-27-5 EC No.: 227-813-5 REACH: Index No.: 601-029-00-7	3-5%	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	[9]
propan-2-ol;isopropyl alcohol;isopropanol	CAS No.: 67-63-0 EC No.: 200-661-7 REACH: Index No.: 603-117-00-0	1-3%	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	
Isobutan	CAS No.: 75-28-5 EC No.: 200-857-2 REACH: Index No.: 601-004-00-0	1-3%	Flam. Gas 1A, H220 Press. Gas (Comp.) H280	
ammonia%	CAS No.: 1336-21-6 EC No.: 215-647-6 REACH: 01-2119982985-14-XXXX Index No.: 007-001-01-2	1-3%	Skin Corr. 1B, H314 STOT SE 3, H335 (SCL: 5.00 %) Aquatic Acute 1, H400 (M=1)	

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

[1] European occupational exposure limit.

[9] Identified by EU as one of 26 specific fragrance ingredients, known to cause allergic contact dermatitis (Regulation (EC) No 1223/2009 on cosmetic products)

[16] Propellant

Labelling of contents according to Detergents Regulation (EC) No 648/2004

15% - 30%

- Anionic surfactants
- < 5%
- Perfumes (D-LIMONENE)

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.

Eye contact

Upon irritation of the eye: Remove contact lenses and open eyes widely. Flush eyes with water or saline water (20-30 °C) for at least 5 minutes. Seek medical assistance and continue flushing during transport.

Ingestion

If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink.

In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

Burns

Rinse with water until pain stops then continue to rinse for 30 minutes.

4.2. Most important symptoms and effects, both acute and delayed

None known.

According to EC-Regulation 2015/830

4.3. Indication of any immediate medical attention and special treatment needed

None known.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Sulphur oxides

Carbon oxides (CO / CO₂)

Some metal oxides

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact the chemical emergency services on 45 90 60 00 (24 h service) in order to obtain further advice.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities.

6.3. Methods and material for containment and cleaning up

Limit spillage and collect using granular absorbent or similar materials, and dispose of it in accordance with the regulations on dangerous waste.

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Because of the danger of self-ignition, any waste from the product, spray mist and soiled rags etc. are to be kept in a fire-proof place in air-tight containers, alternatively the waste is to be burned.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers and store protected from moisture and light. Containers should be dated when opened and tested periodically for the presence of peroxides. Do not exceed storage time limits.

Must be stored in a cool and well-ventilated area, away from possible sources of ignition.

Pressurized gas packs (spray cans, aerosol cans) must be stored behind a wire mesh, which allows gases to escape and holds back packs flying around.

Recommended storage material

Always store in containers of the same material as the original container.

Storage temperature

> 0°C

< 50°C

Protect from sunlight.

Dry, cool and well ventilated

According to EC-Regulation 2015/830

Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Butane

Long term exposure limit (8 hours) (mg/m³): 1200
 Long term exposure limit (8 hours) (ppm): 500
 Short term exposure limit (15 minutes) (mg/m³): 2400
 Short term exposure limit (15 minutes) (ppm): 1000

2-butoxyethanol

Long term exposure limit (8 hours) (mg/m³): 98
 Long term exposure limit (8 hours) (ppm): 20
 Short term exposure limit (15 minutes) (mg/m³): 246
 Short term exposure limit (15 minutes) (ppm): 50

Annotations:

E = Substance has an EC limit.

H = The substance can be absorbed through the skin.

Propane

Long term exposure limit (8 hours) (mg/m³): 1800
 Long term exposure limit (8 hours) (ppm): 1000
 Short term exposure limit (15 minutes) (mg/m³): 3600
 Short term exposure limit (15 minutes) (ppm): 2000

propan-2-ol;isopropyl alcohol;isopropanol

Long term exposure limit (8 hours) (mg/m³): 490
 Long term exposure limit (8 hours) (ppm): 200

Statutory order 202 on exposure limits for substances and mixtures (21/02/2023)

DNEL

(R)-p-mentha-1,8-diene;dipentene;(±)-1-methyl-4-(1-methylvinyl)cyclohexene;(S)-p-mentha-1,8-diene;trans-1-methyl-4-(1-methylvinyl)cyclohexene;d-limonene;limonene;l-limonene

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	4.8 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	9.5 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	16.6 mg/m ³
Long term – Systemic effects - Workers	Inhalation	66.7 mg/m ³
Long term – Systemic effects - General population	Oral	4.8 mg/kg bw/day

2-butoxyethanol

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Inhalation	59 mg/m ³
Long term – Systemic effects - Workers	Inhalation	98 mg/m ³
Short term – Local effects - General population	Inhalation	147 mg/m ³
Short term – Local effects - Workers	Inhalation	246 mg/m ³
Short term – Systemic effects - General population	Inhalation	426 mg/m ³
Short term – Systemic effects - Workers	Inhalation	1091 mg/m ³
Long term – Systemic effects - General population	Oral	6.3 mg/kg bw/day
Short term – Systemic effects - General population	Oral	26.7 mg/kg bw/day

propan-2-ol;isopropyl alcohol;isopropanol

Duration:	Route of exposure:	DNEL:
-----------	--------------------	-------

According to EC-Regulation 2015/830

Long term – Systemic effects - General population	Dermal	319mg/kg bw/dag
Long term – Systemic effects - General population	Dermal	319 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	888 mg/kg bw/dag
Long term – Systemic effects - Workers	Dermal	888 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	89mg/m ³
Long term – Systemic effects - General population	Inhalation	89 mg/m ³
Long term – Systemic effects - Workers	Inhalation	500 mg7m ³
Long term – Systemic effects - Workers	Inhalation	500 mg/m ³
Short term – Systemic effects - General population	Inhalation	178 mg/m ³
Short term – Systemic effects - Workers	Inhalation	1000 mg/m ³
Long term – Systemic effects - General population	Oral	26mg/kg bw/dag
Long term – Systemic effects - General population	Oral	26 mg/kg bw/day
Short term – Systemic effects - General population	Oral	51 mg/kg bw/day

Sulfuric acid, mono-C12-14-alkyl esters, sodium salts

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	2440 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	4060 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	85 mg/m ³
Long term – Systemic effects - Workers	Inhalation	285 mg/m ³
Long term – Systemic effects - General population	Oral	24 mg/kg bw/day

PNEC

(R)-p-mentha-1,8-diene;dipentene;(±)-1-methyl-4-(1-methylvinyl)cyclohexene;(S)-p-mentha-1,8-diene;trans-1-methyl-4-(1-methylvinyl)cyclohexene;d-limonene;limonene;l-limonene

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		14 µg/L
Freshwater sediment		3.85 mg/kg
Marine water		1.4 µg/L
Marine water sediment		385 µg/kg
Predators		133 mg/kg
Sewage treatment plant		1.8 mg/L
Soil		763 µg/kg

2-butoxyethanol

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		8.8 mg/L
Freshwater sediment		34.6 mg/kg
Intermittent release (freshwater)		26.4 mg/L
Marine water		880 µg/L
Marine water sediment		3.46 mg/kg
Predators		20 mg/kg
Sewage treatment plant		463 mg/L
Soil		2.33 mg/kg

propan-2-ol;isopropyl alcohol;isopropanol

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		140,9 mg/l
Freshwater		140.9 mg/L
Freshwater sediment		552 mg/kg

According to EC-Regulation 2015/830

Freshwater sediment	552 mg/kg
Intermittent release	140,9 mg/l
Intermittent release (freshwater)	140.9 mg/L
Marine water	140,9 mg/l
Marine water	140.9 mg/L
Marine water sediment	552mg/kg
Marine water sediment	552 mg/kg
Predators	160 mg/kg
Sewage treatment plant	251 mg/l
Sewage treatment plant	2.251 g/L
Soil	28 mg/kg
Soil	28 mg/kg
Sulfuric acid, mono-C12-14-alkyl esters, sodium salts	
Route of exposure:	Duration of Exposure:
Freshwater	PNEC:
Freshwater sediment	131 µg/L
Intermittent release (freshwater)	4.61 mg/kg
Marine water	36 µg/L
Marine water sediment	13.1 µg/L
Sewage treatment plant	461 µg/kg
Soil	1.35 mg/L
	846 µg/kg

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

Apply standard precautions during use of the product. Avoid inhalation of gas or dust.

Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

Measures to avoid environmental exposure

No specific requirements.

Individual protection measures, such as personal protective equipment

Generally

Take off contaminated clothing and wash it before reuse.
Only CE-marked personal protection equipment should be used.
Use only CE marked protective equipment.

Respiratory Equipment

Type	Class	Colour	Standards
Normally, personal respiratory equipment is not necessary			

Skin protection

Recommended	Type/Category	Standards
Dedicated work clothing should be worn	-	-



According to EC-Regulation 2015/830

Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards
Nitrile	0,11	> 480	EN374-2, EN374-3, EN388



Eye protection

Type	Standards
Safety glasses with side shields.	EN166



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

Aerosol

Colour

Colourless

Odour / Odour threshold

Fruity

pH

11,3

Density (g/cm³)

0.94

Kinematic viscosity

68

Particle characteristics

Testing not relevant or not possible due to the nature of the product.

Phase changes

Melting point/Freezing point (°C)

Testing not relevant or not possible due to the nature of the product.

Softening point/range (waxes and pastes) (°C)

Does not apply to aerosols.

Boiling point (°C)

-44.5

Vapour pressure

Testing not relevant or not possible due to the nature of the product.

Relative vapour density

Testing not relevant or not possible due to the nature of the product.

Decomposition temperature (°C)

Testing not relevant or not possible due to the nature of the product.

Data on fire and explosion hazards

Flash point (°C)

-97

Flammability (°C)

365

Auto-ignition temperature (°C)

Testing not relevant or not possible due to the nature of the product.

Lower and upper explosion limit (% v/v)

Testing not relevant or not possible due to the nature of the product.

Solubility

Solubility in water

Testing not relevant or not possible due to the nature of the product.

n-octanol/water coefficient

Testing not relevant or not possible due to the nature of the product.

Solubility in fat (g/L)

Testing not relevant or not possible due to the nature of the product.

According to EC-Regulation 2015/830

9.2. Other information

Other physical and chemical parameters

No data available.

Oxidizing properties

Testing not relevant or not possible due to the nature of the product.

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Avoid static electricity.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/substance	2-butoxyethanol
Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	1746 mg/kg ·

Product/substance	2-butoxyethanol
Species:	Guinea pig
Route of exposure:	Oral
Test:	LD50
Result:	1414 mg/kg ·

Product/substance	2-butoxyethanol
Species:	Guinea pig
Route of exposure:	Dermal
Test:	LD50
Result:	>2000 mg/kg ·

Product/substance	2-butoxyethanol
Species:	Rat
Route of exposure:	Inhalation
Test:	LC50
Result:	>3,1 mg/l ·

Product/substance	propan-2-ol;isopropyl alcohol;isopropanol
Species:	Rabbit
Route of exposure:	Dermal
Test:	LD50
Result:	>2000 mg/kg ·

Product/substance	propan-2-ol;isopropyl alcohol;isopropanol
Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	5840 mg/kg ·

Product/substance	propan-2-ol;isopropyl alcohol;isopropanol
Species:	Rat

According to EC-Regulation 2015/830

Route of exposure:	Inhalation
Test:	LC50
Result:	66,1mg/l 4 h ·

Product/substance	propan-2-ol;isopropyl alcohol;isopropanol
Species:	Rat
Route of exposure:	Inhalation
Test:	LC50
Result:	47,5mg/l 8 h ·

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Based on available data, the classification criteria are not met.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

May cause an allergic skin reaction.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Long term effects

None known.

Endocrine disrupting properties

Not applicable.

Other information

2-butoxyethanol has been classified by IARC as a group 3 carcinogen.

(R)-p-mentha-1,8-diene;dipentene;(±)-1-methyl-4-(1-methylvinyl)cyclohexene;(S)-p-mentha-1,8-diene;trans-1-methyl-4-(1-methylvinyl)cyclohexene;d-limonene;limonene;l-limonene has been classified by IARC as a group 3 carcinogen.

propan-2-ol;isopropyl alcohol;isopropanol has been classified by IARC as a group 3 carcinogen.

SECTION 12: Ecological information

12.1. Toxicity

Product/substance	2-butoxyethanol
Species:	Fish
Duration:	96 hours
Test:	LC50
Result:	1474 mg/l ·

Product/substance	2-butoxyethanol
Species:	Daphnia
Duration:	48 hours
Test:	EC50
Result:	1550mg/l ·

Product/substance	2-butoxyethanol
Species:	Algae
Duration:	72 hours
Test:	EC50
Result:	1840 /lmg ·

Product/substance	2-butoxyethanol
-------------------	-----------------

According to EC-Regulation 2015/830

Species: Crustacean
 Duration: 16 hours
 Test: EC0
 Result: 700 mg/l ·

Product/substance: propan-2-ol;isopropyl alcohol;isopropanol
 Species: Algae
 Duration: 8 days
 Test: NOEC
 Result: >1800 mg/l ·

Product/substance: propan-2-ol;isopropyl alcohol;isopropanol
 Species: Fish
 Duration: 96 hours
 Test: LC50
 Result: 8970-9280 mg/l ·

Product/substance: propan-2-ol;isopropyl alcohol;isopropanol
 Species: Daphnia
 Duration: 24 hours
 Test: EC50
 Result: 9714 mg/l ·

Product/substance: propan-2-ol;isopropyl alcohol;isopropanol
 Species: Crustacean
 Duration: 18 hours
 Test: EC10
 Result: 5175 mg/l ·

Product/substance: propan-2-ol;isopropyl alcohol;isopropanol
 Species: Crustacean
 Duration: No data available.
 Test: EC50
 Result: >1000mg/l ·

Product/substance: Isobutan
 Species: Algae
 Duration: 72 hours
 Test: EC50
 Result: 8,6 mg/l ·

Product/substance: Isobutan
 Species: Daphnia
 Duration: 48 hours
 Test: EC50
 Result: 16,3 mg/l ·

Product/substance: Isobutan
 Species: Fish
 Duration: 96 hours
 Test: LC50
 Result: 28 mg/kg ·

12.2. Persistence and degradability

Product/substance: 2-butoxyethanol
 Biodegradable: Yes
 Test method:
 Result:

Product/substance: propan-2-ol;isopropyl alcohol;isopropanol
 Biodegradable: Yes
 Test method: OECD 301 E
 Result: 95%

Product/substance: Isobutan
 Biodegradable: Yes

According to EC-Regulation 2015/830

Test method:
Result:

12.3. Bioaccumulative potential

Product/substance 2-butoxyethanol
Test method:
Potential bioaccumulation: No
LogPow: 0,8100
BCF: No data available.
Other information:

Product/substance propan-2-ol;isopropyl alcohol;isopropanol
Test method:
Potential bioaccumulation: No
LogPow: No data available.
BCF: No data available.
Other information:

Product/substance Isobutan
Test method:
Potential bioaccumulation: No
LogPow: No data available.
BCF: No data available.
Other information:

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

12.6. Endocrine disrupting properties

Not applicable.

12.7. Other adverse effects

This product contains substances that are toxic to the environment. May result in adverse effects to aquatic organisms.

This product contains substances, which may cause adverse long-term effects to the aquatic environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product is covered by the regulations on hazardous waste.

To the extent the material has not been subject to regular tests of peroxide formation the waste shall be treated as explosive waste.

HP 3 - Flammable

HP 4 - Irritant (skin irritation and eye damage)

HP 6 - Acute toxicity

Commission Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

EWC code

16 05 04* Gases in pressure containers (including halons) containing dangerous substances

Waste group

16 05 04* Gases in pressure containers (including halons) containing dangerous substances

Specific labelling

Not applicable.




Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
ADR	UN1950	AEROSOLS	Class: 2 Labels: 2.1 Classification code: 5F	-	Yes	Limited quantities: 1 L Tunnel

According to EC-Regulation 2015/830

14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
					restriction code: (D) See below for additional information.
IMDG	UN1950 AEROSOLS	Class: 2 Labels: 2.1 Classification code: 5F style="text-align: center;"> 	-	Yes	Limited quantities: 1 L EmS: F-D S-U See below for additional information.
IATA	UN1950 AEROSOLS	Class: 2 Labels: 2.1 Classification code: 5F style="text-align: center;"> 	-	Yes	See below for additional information.

* Packing group

** Environmental hazards

Additional information

ADR / See Table A, Section 3.2.1 for any information on special provisions, requirements, or warnings in connection with transport. See section 5.4.3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.

IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.

IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.

This product is within scope of the regulations of transport of dangerous goods.

14.6. Special precautions for user

Not applicable.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

People under the age of 18 shall not be exposed to this product.

Demands for specific education

No specific requirements.

SEVESO - Categories / dangerous substances

P3a - FLAMMABLE AEROSOLS, Qualifying quantity (lower-tier): 150 tonnes (net) / (upper-tier): 500 tonnes (net)

Additional information

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No 648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

Code number (1993): 00-1

Sources

The Danish Working Environment Authority's executive order no. 239 of 6 April 2005 on young people's work. Based on Council Directive 94/33 / EC of 22 June 1994 on the protection of young people at work.

Pregnant workers and workers who are breastfeeding (AT Guide A.1.8-6, amended 2020).

Executive Order no. 247 of 14 March 2014 on interior design, etc. of aerosols, as amended by EO No. 301 of 27 March 2014, EO no. 478 of 25 May 2016 and EO 1336 of 29 November 2017.

Regulation (EC) No 648/2004 of the European Parliament and of the Council of 31 March 2004 on detergents.

Executive Order no. 372 of 25 April 2016 on control of the risk of major accidents with dangerous substances.

Commission Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

According to EC-Regulation 2015/830

Arbejdstilsynets bekendtgørelse nr. 301 af 13. maj 1993 om fastsættelse af kodenumre med senere ændringer.
 Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (CLP).
 Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

H220, Extremely flammable gas.
 H225, Highly flammable liquid and vapour.
 H226, Flammable liquid and vapour.
 H280, Contains gas under pressure; may explode if heated.
 H302, Harmful if swallowed.
 H312, Harmful in contact with skin.
 H314, Causes severe skin burns and eye damage.
 H315, Causes skin irritation.
 H317, May cause an allergic skin reaction.
 H318, Causes serious eye damage.
 H319, Causes serious eye irritation.
 H332, Harmful if inhaled.
 H335, May cause respiratory irritation.
 H336, May cause drowsiness or dizziness.
 H400, Very toxic to aquatic life.
 H410, Very toxic to aquatic life with long lasting effects.
 H412, Harmful to aquatic life with long lasting effects.

The full text of identified uses as mentioned in section 1

LCS "PW" = Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
 LCS "C" = Consumer uses: Private households (= general public = consumers)
 PROC 11 = Non industrial spraying
 PC 35 = Washing and Cleaning Products (including solvent based products)
 ERC 8a = Wide dispersive indoor use of processing aids in open systems

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
 ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
 ATE = Acute Toxicity Estimate
 BCF = Bioconcentration Factor
 CAS = Chemical Abstracts Service
 CE = Conformité Européenne
 CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
 CSA = Chemical Safety Assessment
 CSR = Chemical Safety Report
 DMEL = Derived Minimal Effect Level
 DNEL = Derived No Effect Level
 EINECS = European Inventory of Existing Commercial chemical Substances
 ES = Exposure Scenario
 EUH statement = CLP-specific Hazard statement
 EWC = European Waste Catalogue
 GHS = Globally Harmonized System of Classification and Labelling of Chemicals
 IARC = International Agency for Research on Cancer (IARC)
 IATA = International Air Transport Association
 IBC = Intermediate Bulk Container
 IMDG = International Maritime Dangerous Goods
 LogPow = logarithm of the octanol/water partition coefficient
 MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
 OECD = Organisation for Economic Co-operation and Development
 PBT = Persistent, Bioaccumulative and Toxic
 PNEC = Predicted No Effect Concentration
 RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
 RRN = REACH Registration Number
 SCL = A specific concentration limit

According to EC-Regulation 2015/830

SVHC = Substances of Very High Concern

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TWA = Time weighted average

UN = United Nations

UVBC = Unknown or variable composition, complex reaction products or of biological materials

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the mixture in regard to physical hazards has been based on experimental data.

The safety data sheet is validated by

Lisbet Tetsche

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: DK-en