

SAFETY DATA SHEET

Universal Spray Glue

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

Universal Spray Glue

▼ Unique formula identifier (UFI)

1ESG-E8PK-7KJM-P503

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Tætningsmasse

Use descriptors (REACH)

Sectors of use	Description
LCS "PW"	Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
LCS "C"	Consumer uses: Private households (= general public = consumers)
Product category	Description
PC 1	Adhesives, Sealants
Process category	Description
PROC 11	Non industrial spraying
Environmental release category	Description
ERC 8a	Wide dispersive indoor use of processing aids in open systems

Uses advised against

None known.

1.3. Details of the supplier of the safety data sheet

Company and address

Pureno A/S

Rønnevangs Alle 8

3400 Hillerød

Denmark

+45 70 260 267

Contact person

Kenneth Christensen

E-mail

kc@pureno.dk

Revision

5/11/2023

SDS Version

2.0

Date of previous version

4/19/2023 (1.0)

1.4. Emergency telephone number

Contact the poison hotline: +45 82 12 12 12 (24 hour service)

See section 4 "First aid measures".

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Aerosol 1; H222, H229, Extremely flammable aerosol. Pressurised container: May burst if heated.

Eye Irrit. 2; H319, Causes serious eye irritation.

STOT SE 3; H336, May cause drowsiness or dizziness.

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Aquatic Chronic 3; H412, Harmful to aquatic life with long lasting effects.

2.2. Label elements

Hazard pictogram(s)



Signal word

Danger

Hazard statement(s)

Extremely flammable aerosol. Pressurised container: May burst if heated. (H222, H229)

Causes serious eye irritation. (H319)

May cause drowsiness or dizziness. (H336)

Harmful to aquatic life with long lasting effects. (H412)

Precautionary statement(s)

General

-

Prevention

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. (P210)

Do not spray on an open flame or other ignition source. (P211)

Response

Call a POISON CENTER/doctor if you feel unwell. (P312)

If eye irritation persists: Get medical advice/attention. (P337+P313)

Storage

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F. (P410+P412)

Disposal

Dispose of contents/container in accordance with local regulation. (P501)

Hazardous substances

Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane
acetone;propan-2-one;propanone

▼ Additional labelling

UFI: 1ESG-E8PK-7KJM-P503

VOC

VOC content: 535 g/L

MAXIMUM VOC CONTENT (Phase II, category A/h (SB): 750 g/L)

2.3. Other hazards

Additional warnings

In the event of leaks, high concentrations of gases can quickly form. They can be toxic, asphyxiating, or explosive.

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable. This product is a mixture.

3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
Petroleum gases, liquefied; Petroleum gas; [A complex combination of hydrocarbons produced by the distillation of crude oil. It consists of hydrocarbons having carbon numbers predominantly in the range of C3 through C7 and boiling in the range of approximately -40 °C to 80 °C (-40 °F to 176 °F).]	CAS No.: 68476-85-7 EC No.: 270-704-2 REACH: 01-2119485911-31-XXXX Index No.: 649-202-00-6	40-60%	Flam. Gas 1A, H220 Press. Gas (Liq.), H280	[19]

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	CAS No.: EC No.: 926-605-8 REACH: 01-2119486291-36-XXXX Index No.:	15-25%	EUH066 Flam. Liq. 2, H225 Asp. Tox. 1, H304 STOT SE 3, H336 Aquatic Chronic 2, H411	
acetone;propan-2-one;propanone	CAS No.: 67-64-1 EC No.: 200-662-2 REACH: 01-2119471330-49-XXXX Index No.: 606-001-00-8	15-25%	EUH066 Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	[1]

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

[1] European occupational exposure limit.

[19] UVCB = Unknown or variable composition, complex reaction products or of biological materials

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

Upon irritation: rinse with water. In the event of continued irritation, seek medical assistance.

Eye contact

Upon irritation of the eye: Remove contact lenses. Flush eyes immediately with plenty of water or isotonic water (20-30 °C) for at least 5 minutes and continue until irritation stops. Make sure to flush under upper and lower eyelids. If irritation continues, contact a doctor. Continue flushing during transport.

Ingestion

If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink.

In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

Burns

Rinse with water until pain stops then continue to rinse for 30 minutes.

4.2. Most important symptoms and effects, both acute and delayed

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

4.3. Indication of any immediate medical attention and special treatment needed

If eye irritation persists: Get medical advice/attention.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO₂)

5.3. Advice for firefighters

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact the chemical emergency services on 45 90 60 00 (24 h service) in order to obtain further advice.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.

Avoid inhalation of vapours from spilled material.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities.

6.3. Methods and material for containment and cleaning up

Limit spillage and collect using granular absorbent or similar materials, and dispose of it in accordance with the regulations on dangerous waste.

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Must be stored in a cool and well-ventilated area, away from possible sources of ignition.

Pressurized gas packs (spray cans, aerosol cans) must be stored behind a wire mesh, which allows gases to escape and holds back packs flying around.

Recommended storage material

Always store in containers of the same material as the original container.

Storage temperature

> 0°C

< 50°C

Dry, cool and well ventilated

Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

acetone;propan-2-one;propanone

Long term exposure limit (8 hours) (mg/m³): 600

Long term exposure limit (8 hours) (ppm): 250

Short term exposure limit (15 minutes) (mg/m³): 1200

Short term exposure limit (15 minutes) (ppm): 500

Annotations:

E = Substance has an EC limit.

Statutory order 202 on exposure limits for substances and mixtures (21/02/2023)

DNEL

acetone;propan-2-one;propanone

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	62 mg/kg bw/day
Long term – Systemic effects - General population	Dermal	62 mg/kg bw/day

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Long term – Systemic effects - Workers	Dermal	186mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	186 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	200mg/m ³
Long term – Systemic effects - General population	Inhalation	200 mg/m ³
Long term – Systemic effects - Workers	Inhalation	1210 mg/m ³
Long term – Systemic effects - Workers	Inhalation	1210 mg/m ³
Short term – Local effects	Inhalation	2420 mg/m ³
Short term – Local effects - Workers	Inhalation	2420 mg/m ³
Long term – Systemic effects - General population	Oral	62 mg/kg bw/day
Long term – Systemic effects - General population	Oral	62 mg/kg bw/day

Petroleum gases, liquefied;Petroleum gas;[A complex combination of hydrocarbons produced by the distillation of crude oil. It consists of hydrocarbons having carbon numbers predominantly in the range of C3 through C7 and boiling in the range of approximately – 40 °C to 80 °C (– 40 °F to 176 °F).]

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - Workers	Dermal	23.4 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	66.4 µg/m ³
Long term – Systemic effects - Workers	Inhalation	2.21 mg/m ³

PNEC

acetone;propan-2-one;propanone

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		10,6 mg/l
Freshwater		10.6 mg/L
Freshwater sediment		30,4mg/kg
Freshwater sediment		30.4 mg/kg
Intermittent release (freshwater)		21 mg/L
Marine water		1,06 mg/l
Marine water		1.06 mg/L
Marine water sediment		3,04 mg/kg
Marine water sediment		3.04 mg/kg
Sewage treatment plant		100 mg/L
Soil		29,5 mg/kg
Soil		29.5 mg/kg

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

Apply standard precautions during use of the product. Avoid inhalation of gas or dust.

Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

Measures to avoid environmental exposure

Provide adequate general and local exhaust ventilation.

Individual protection measures, such as personal protective equipment

Generally

Use only CE marked protective equipment.

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Respiratory Equipment

Type	Class	Colour	Standards
Normally, personal respiratory equipment is not necessary			

Skin protection

Recommended	Type/Category	Standards
Dedicated work clothing should be worn	-	-



Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards
Nitrile	0.3	> 60	EN374-2, EN374-3, EN388



Eye protection

Type	Standards
Safety glasses	EN166



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

Aerosol

Colour

Amber

Odour / Odour threshold

Characteristic

pH

Not applicable - product is an aerosol

Density (g/cm³)

0.8

Kinematic viscosity

100 - 300

Particle characteristics

Testing not relevant or not possible due to the nature of the product.

Phase changes

Melting point/Freezing point (°C)

Testing not relevant or not possible due to the nature of the product.

Softening point/range (waxes and pastes) (°C)

Does not apply to aerosols.

Boiling point (°C)

Testing not relevant or not possible due to the nature of the product.

Vapour pressure

Testing not relevant or not possible due to the nature of the product.

Relative vapour density

Testing not relevant or not possible due to the nature of the product.

Decomposition temperature (°C)

Testing not relevant or not possible due to the nature of the product.

Data on fire and explosion hazards

Flash point (°C)

< 60

Flammability (°C)

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

The material is ignitable.

Auto-ignition temperature (°C)

Testing not relevant or not possible due to the nature of the product.

Lower and upper explosion limit (% v/v)

Testing not relevant or not possible due to the nature of the product.

Solubility

Solubility in water

Testing not relevant or not possible due to the nature of the product.

n-octanol/water coefficient

Testing not relevant or not possible due to the nature of the product.

Solubility in fat (g/L)

Testing not relevant or not possible due to the nature of the product.

9.2. Other information

VOC (g/L)

535

Other physical and chemical parameters

No data available.

Oxidizing properties

Testing not relevant or not possible due to the nature of the product.

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Avoid static electricity.

Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/substance	acetone;propan-2-one;propanone
Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	5800 mg/kg ·

Product/substance	acetone;propan-2-one;propanone
Species:	Rat
Route of exposure:	Dermal
Test:	LD50
Result:	15800 mg/kg ·

Product/substance	acetone;propan-2-one;propanone
Species:	Rat
Route of exposure:	Inhalation
Test:	LC50
Result:	76 mg/kg 4 h ·

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Causes serious eye irritation.

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Long term effects

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

Endocrine disrupting properties

Not applicable.

Other information

None known.

SECTION 12: Ecological information

12.1. Toxicity

Product/substance	acetone;propan-2-one;propanone
Species:	Daphnia
Duration:	48 hours
Test:	EC50
Result:	>100 mg/l ·

Product/substance	acetone;propan-2-one;propanone
Species:	Fish
Duration:	96 hours
Test:	LC50
Result:	>100 mg/l ·

Product/substance	acetone;propan-2-one;propanone
Species:	Algae
Duration:	96 hours
Test:	EC50
Result:	>100 mg/l ·

12.2. Persistence and degradability

Product/substance	acetone;propan-2-one;propanone
Biodegradable:	Yes
Test method:	OECD 301 B
Result:	90,9

12.3. Bioaccumulative potential

Product/substance	acetone;propan-2-one;propanone
Test method:	
Potential bioaccumulation:	No
LogPow:	No data available.
BCF:	No data available.
Other information:	

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

12.6. Endocrine disrupting properties

Not applicable.

12.7. Other adverse effects

This product contains substances that are toxic to the environment. May result in adverse effects to aquatic organisms.

This product contains substances, which may cause adverse long-term effects to the aquatic environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product is covered by the regulations on hazardous waste.

HP 3 - Flammable

HP 4 - Irritant (skin irritation and eye damage)

HP 14 - Ecotoxic

Dispose of contents/container to an approved waste disposal plant.

Commission Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

EWC code

16 05 04* Gases in pressure containers (including halons) containing dangerous substances

Waste group

16 05 04* Gases in pressure containers (including halons) containing dangerous substances

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
ADR	UN1950	AEROSOLS	Transport hazard class: 2 Label: 2.1 Classification code: 5F 	-	No	Limited quantities: 1 L Tunnel restriction code: (D) See below for additional information.
IMDG	UN1950	AEROSOLS	Transport hazard class: 2 Label: 2.1 Classification code: 5F 	-	No	Limited quantities: 1 L EmS: F-D S-U See below for additional information.
IATA	UN1950	AEROSOLS	Transport hazard class: 2 Label: 2.1 Classification code: 5F 	-	No	See below for additional information.

* Packing group

** Environmental hazards

Additional information

ADR / See Table A, Section 3.2.1 for any information on special provisions, requirements, or warnings in connection with transport. See section 5.4.3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.

IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.

IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.

This product is within scope of the regulations of transport of dangerous goods.

14.6. Special precautions for user

Not applicable.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

Restricted to professional users.

People under the age of 18 shall not be exposed to this product.

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

Demands for specific education

No specific requirements.

SEVESO - Categories / dangerous substances

P3a - FLAMMABLE AEROSOLS, Qualifying quantity (lower-tier): 150 tonnes (net) / (upper-tier): 500 tonnes (net)

Regulation on drug precursors

acetone;propan-2-one;propanone is included (Category 3)

Regulation on explosives precursors

acetone;propan-2-one;propanone (Annex II)

Additional information

Not applicable.

Sources

The Danish Working Environment Authority's executive order no. 239 of 6 April 2005 on young people's work.

Based on Council Directive 94/33 / EC of 22 June 1994 on the protection of young people at work.

Pregnant workers and workers who are breastfeeding (AT Guide A.1.8-6, amended 2020).

Executive Order no. 247 of 14 March 2014 on interior design, etc. of aerosols, as amended by EO No. 301 of 27 March 2014, EO no. 478 of 25 May 2016 and EO 1336 of 29 November 2017.

Executive Order no. 372 of 25 April 2016 on control of the risk of major accidents with dangerous substances.

Executive Order no. 1369 of 25 November 2015 on the marketing and labeling of volatile organic compounds in certain paints and varnishes as well as products for car repair painting.

Commission Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

Council Regulation (EC) No 273/2004 on drug precursors.

Council Regulation (EC) No 2019/1148 on explosives precursors.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (CLP).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

H220, Repeated exposure may cause skin dryness or cracking.

H220, Extremely flammable gas.

H225, Highly flammable liquid and vapour.

H280, Contains gas under pressure; may explode if heated.

H304, May be fatal if swallowed and enters airways.

H319, Causes serious eye irritation.

H336, May cause drowsiness or dizziness.

H411, Toxic to aquatic life with long lasting effects.

The full text of identified uses as mentioned in section 1

LCS "PW" = Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

LCS "C" = Consumer uses: Private households (= general public = consumers)

PROC 11 = Non industrial spraying

PC 1 = Adhesives, Sealants

ERC 8a = Wide dispersive indoor use of processing aids in open systems

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

BCF = Bioconcentration Factor
 CAS = Chemical Abstracts Service
 CE = Conformité Européenne
 CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
 CSA = Chemical Safety Assessment
 CSR = Chemical Safety Report
 DMEL = Derived Minimal Effect Level
 DNEL = Derived No Effect Level
 EINECS = European Inventory of Existing Commercial chemical Substances
 ES = Exposure Scenario
 EUH statement = CLP-specific Hazard statement
 EWC = European Waste Catalogue
 GHS = Globally Harmonized System of Classification and Labelling of Chemicals
 IARC = International Agency for Research on Cancer (IARC)
 IATA = International Air Transport Association
 IBC = Intermediate Bulk Container
 IMDG = International Maritime Dangerous Goods
 LogPow = logarithm of the octanol/water partition coefficient
 MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
 OECD = Organisation for Economic Co-operation and Development
 PBT = Persistent, Bioaccumulative and Toxic
 PNEC = Predicted No Effect Concentration
 RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
 RRN = REACH Registration Number
 SCL = A specific concentration limit
 SVHC = Substances of Very High Concern
 STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
 STOT-SE = Specific Target Organ Toxicity - Single Exposure
 TWA = Time weighted average
 UN = United Nations
 UVBC = Unknown or variable composition, complex reaction products or of biological materials
 VOC = Volatile Organic Compound
 vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the mixture in regard of health hazards is in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP).

The classification of the substance/mixture in regard of environmental hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP).

The classification of the mixture in regard to physical hazards has been based on experimental data.

▼ **The safety data sheet is validated by**

Lisbet Tetsche

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: DK-en