SAFETY DATA SHEET

Superlim CA-320

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

Superlim CA-320

Unique formula identifier (UFI)

JM5M-DHU1-W208-TNEW

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Tætningsmasse

Use descriptors (REACH)

Sectors of use	Description
LCS "C"	Consumer uses: Private households (= general public = consumers)
LCS "PW"	Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Product category	**Description**
PC 1	Adhesives, Sealants
Process category	**Description**
PROC 10	Roller application or brushing
Environmental release category	**Description**
ERC 8a	Wide dispersive indoor use of processing aids in open systems

Uses advised against

None known.

1.3. Details of the supplier of the safety data sheet

Company and address

Pureno A/S
Gefionsvej 20
3400 Hillerød
Denmark
+45 70 260 267

Contact person

Lars Skaarup

E-mail

ls@pureno.dk

Revision

18/02/2025

SDS Version

2.0

Date of previous version

18/02/2025 (1.0)

1.4. Emergency telephone number

Contact the poison hotline: +45 82 12 12 12 (24 hour service)
See section 4 “First aid measures”.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Skin Irrit. 2; H315, Causes skin irritation.
Eye Irrit. 2; H319, Causes serious eye irritation.

STOT SE 3; H335, May cause respiratory irritation.

2.2. Label elements

Hazard pictogram(s)

Signal word

Warning

Hazard statement(s)

Causes skin irritation. (H315)
Causes serious eye irritation. (H319)
May cause respiratory irritation. (H335)

Precautionary statement(s)

General

If medical advice is needed, have product container or label at hand. (P101)
Keep out of reach of children. (P102)

▼Prevention

Wash hands thoroughly after handling. (P264)
Wear eye protection/protective gloves/protective clothing. (P280)

Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. (P305+P351+P338)
If eye irritation persists: Get medical advice/attention. (P337+P313)

Storage

Store locked up. (P405)

Disposal

Dispose of contents/container in accordance with local regulation
(P501)

Hazardous substances

ethyl 2-cyanoacrylate

Additional labelling

EUH202, Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the reach of children.
EUH208, Contains 1,4-dihydroxybenzene;hydroquinone;quinol. May produce an allergic reaction.

UFI: JM5M-DHU1-W208-TNEW

2.3. Other hazards

Additional warnings

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.
This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2023/707.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable. This product is a mixture.

3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
ethyl 2-cyanoacrylate	CAS No.: 7085-85-0 EC No.: 230-391-5 REACH: 01-2119527766-29-XXXX Index No.: 607-236-00-9	95-100%	Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335	
1,4-dihydroxybenzene;hydroquinone;quinol	CAS No.: 123-31-9 EC No.: 204-617-8 REACH: 01-2119524016-51-XXXX Index No.: 604-005-00-4	<1%	Acute Tox. 4, H302 Skin Sens. 1, H317 Eye Dam. 1, H318 Muta. 2, H341 Carc. 2, H351 Aquatic Acute 1, H400 (M=10)	

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

-

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

Do NOT pull bonded skin apart. Gently peel apart, preferably after soaking in warm, soapy water.
Do not pull solidified product away from the skin.

Eye contact

If the eyelid is bonded closed, do not force open. Cover with a wet pad soaked in warm water until debonding is complete, usually 1-3 days.

Ingestion

If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink.
In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

Burns

Not applicable.

4.2. Most important symptoms and effects, both acute and delayed

Headache, Methaemoglobinaemia (1,4-dihydroxybenzene;hydroquinone;quinol)
Sensitisation: This product contains substances, which may trigger allergic reaction upon dermal contact. Manifestation of allergic reactions typically takes place within 12-72 hours after exposure.
Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

4.3. Indication of any immediate medical attention and special treatment needed

If eye irritation persists: Get medical advice/attention.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.
Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.
If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:
Nitrogen oxides (NO_x)
Carbon oxides (CO / CO2)

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact the chemical emergency services on 72 85 20 00 (24 h service) in order to obtain further advice.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures
Avoid direct contact with spilled substances.
Ensure adequate ventilation, especially in confined areas.
Avoid inhalation of vapours from spilled material.
Contaminated areas may be slippery.

6.2. Environmental precautions
Avoid discharge to lakes, streams, sewers, etc.
Keep unauthorized persons away from the spill

6.3. Methods and material for containment and cleaning up
Limit spillage and collect using granular absorbent or similar materials, and dispose of it in accordance with the regulations on dangerous waste.
Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.
Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections
See section 13 “Disposal considerations” on handling of waste.
See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling
Avoid contact during pregnancy and while nursing.
Smoking, drinking and consumption of food is not allowed in the work area.
See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. ▼Conditions for safe storage, including any incompatibilities
Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

▼Recommended storage material
Keep only in original packaging.

▼Fire class
In accordance with the statutory order on flammable liquids the product is classified as a liquid of class III, subclass 1 (1 storage unit = 50 liter).

▼Storage conditions
Dry, cool and well ventilated

Incompatible materials
Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)
This product should only be used for applications quoted in section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters
ethyl 2-cyanoacrylate
Long term exposure limit (8 hours) (mg/m^3): 10
Long term exposure limit (8 hours) (ppm): 2
Short term exposure limit (15 minutes) (mg/m^3): 20
Short term exposure limit (15 minutes) (ppm): 4

1,4-dihydroxybenzene;hydroquinone;quinol
Short term exposure limit (15 minutes) (mg/m^3): 2
Annotations:
K = The substance may cause cancer.
L = The limit is a ceiling value that at no time may be exceeded.

Statutory order 1619 on exposure limits for substances and mixtures (19/12/2024)

1,4-dihydroxybenzene;hydroquinone;quinol is included in the national list of substances suspected of causing cancer

BEK no. 290 of 19/03/2024 on measures to prevent the risk when working with carcinogenic, mutagenic or reproductively toxic substances and materials.

DNEL

1,4-dihydroxybenzene;hydroquinone;quinol

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	1.66 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	3.33 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	1.05 mg/m^3
Long term – Systemic effects - Workers	Inhalation	2.1 mg/m^3
Long term – Systemic effects - General population	Oral	600 µg/kg bw/day

ethyl 2-cyanoacrylate

Duration:	Route of exposure:	DNEL:
Long term – Local effects - General population	Inhalation	9.25 mg/m^3
Long term – Local effects - Workers	Inhalation	9.25 mg/m^3
Long term – Systemic effects - General population	Inhalation	9.25 mg/m^3
Long term – Systemic effects - Workers	Inhalation	9.25 mg/m^3
Short term – Local effects - General population	Inhalation	9.25 mg/m^3
Short term – Local effects - Workers	Inhalation	9.25 mg/m^3
Short term – Systemic effects - General population	Inhalation	9.25 mg/m^3
Short term – Systemic effects - Workers	Inhalation	9.25 mg/m^3

PNEC

1,4-dihydroxybenzene;hydroquinone;quinol

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		570 ng/L
Freshwater sediment		4.9 µg/kg
Intermittent release (freshwater)		1.34 µg/L
Marine water		57 ng/L
Marine water sediment		490 ng/kg
Sewage treatment plant		710 µg/L
Soil		640 ng/kg

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked.

Apply standard precautions during use of the product. Avoid inhalation of vapours.

Hygiene measures

Take off contaminated clothing and wash it before reuse.

Measures to avoid environmental exposure

No specific requirements.

Individual protection measures, such as personal protective equipment

Generally

Use only CE marked protective equipment.

Respiratory Equipment

Type	Class	Colour	Standards
Under expected normal operating conditions with sufficient ventilation, no respiratory protection is recommended			

▼Skin protection

Recommended	Type/Category	Standards
Dedicated work clothing should be worn	-	-

Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards
Nitrile	0,11	> 480	EN374-2, EN374-3, EN388

Eye protection

Type	Standards
Safety glasses	EN166

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state
Liquid

Colour
Colourless

Odour / Odour threshold
Characteristic

▼pH
No relevant or available data due to the nature of the product.

▼Density (g/cm^3)
1.05

Kinematic viscosity
No relevant or available data due to the nature of the product.

Particle characteristics
Does not apply to liquids.

Phase changes

Melting point/Freezing point (°C)
No relevant or available data due to the nature of the product.

Softening point/range (°C)
Does not apply to liquids.

▼Boiling point (°C)
No relevant or available data due to the nature of the product.

Vapour pressure
No relevant or available data due to the nature of the product.

Relative vapour density
No relevant or available data due to the nature of the product.

Decomposition temperature (°C)
No relevant or available data due to the nature of the product.

Data on fire and explosion hazards

Flash point (°C)

85

Flammability (°C)

No relevant or available data due to the nature of the product.

Auto-ignition temperature (°C)

No relevant or available data due to the nature of the product.

Lower and upper explosion limit (% v/v)

No relevant or available data due to the nature of the product.

Solubility

▼Solubility in water

Insoluble

n-octanol/water coefficient (LogKow)

No relevant or available data due to the nature of the product.

Solubility in fat (g/L)

No relevant or available data due to the nature of the product.

9.2. Other information

Other physical and chemical parameters

No data available.

Oxidizing properties

No relevant or available data due to the nature of the product.

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 “Handling and storage”.

10.3. Possibility of hazardous reactions

Development of heat will occur upon polymerisation of larger quantities of the material

10.4. Conditions to avoid

Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

This product contains substances that may trigger an allergic reaction in already sensitized persons.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Long term effects

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.
Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

Endocrine disrupting properties

This mixture/product does not contain any substances known to have hormone-disrupting properties in relation to health.

Other information

1,4-dihydroxybenzene;hydroquinone;quinol has been classified by IARC as a group 3 carcinogen.

SECTION 12: Ecological information

12.1. Toxicity

No data available.

12.2. Persistence and degradability

Based on available data, the classification criteria are not met.

12.3. Bioaccumulative potential

Based on available data, the classification criteria are not met.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

12.6. Endocrine disrupting properties

This mixture/product does not contain any substances considered to have endocrine-disrupting properties in relation to the environment.

12.7. Other adverse effects

This product contains substances that are toxic to the environment. May result in adverse effects to aquatic organisms.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product is covered by the regulations on hazardous waste. (*)
HP 4 - Irritant (skin irritation and eye damage)
HP 5 - Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
Dispose of contents/container to an approved waste disposal plant.
Commission Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

EWC code

20 01 13*	Solvents

Waste group

20 01 13*	Solvents

Specific labelling

Not applicable.

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
ADR	-	-	-	-	-	-
IMDG	-	-	-	-	-	-
IATA	-	-	-	-	-	-

* Packing group

** Environmental hazards

Additional information

Not dangerous goods according to ADR, IATA and IMDG.

14.6. Special precautions for user

Not applicable.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

People under the age of 18 shall not be exposed to this product.
Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.
Must not be used by persons suffering from acrylic dermatitis.

Demands for specific education

No specific requirements.

SEVESO - Categories / dangerous substances

Not applicable.

Additional information

Not applicable.

Sources

The Danish Working Environment Authority's executive order no. 1049 of 30 May 2021 on young people's work.
Based on Council Directive 94/33 / EC of 22 June 1994 on the protection of young people at work.
Pregnant workers and workers who are breastfeeding (AT Guide A.1.8-6, amended 2024).
Commission Regulation (EU) No 1357/2014 of 18 December 2014 on waste.
Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (CLP).
Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

H302, Harmful if swallowed.
H315, Causes skin irritation.
H317, May cause an allergic skin reaction.
H318, Causes serious eye damage.
H319, Causes serious eye irritation.
H335, May cause respiratory irritation.
H341, Suspected of causing genetic defects.
H351, Suspected of causing cancer.
H400, Very toxic to aquatic life.

The full text of identified uses as mentioned in section 1

LCS "C" = Consumer uses: Private households (= general public = consumers)
LCS "PW" = Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
PROC 10 = Roller application or brushing
PC 1 = Adhesives, Sealants

ERC 8a = Wide dispersive indoor use of processing aids in open systems

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
CAS = Chemical Abstracts Service
CE = Conformité Européenne (European conformity)
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
CSA = Chemical Safety Assessment
CSR = Chemical Safety Report
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EINECS = European Inventory of Existing Commercial chemical Substances
ES = Exposure Scenario
EUH statement = CLP-specific Hazard statement
EuPCS = European Product Categorisation System
EWC = European Waste Catalogue
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
GWP = Global warming potential
IARC = International Agency for Research on Cancer (IARC)
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
OECD = Organisation for Economic Co-operation and Development
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
RRN = REACH Registration Number
SCL = A specific concentration limit
SVHC = Substances of Very High Concern
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
STOT-SE = Specific Target Organ Toxicity - Single Exposure
TWA = Time weighted average
UN = United Nations
UVBC = Unknown or variable composition, complex reaction products or of biological materials
VOC = Volatile Organic Compound
vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the mixture in regard of health hazards is in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP).

The safety data sheet is validated by

Lisbet Tetsche

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.
The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.
It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.
Country-language: DK-en