

SAFETY DATA SHEET

Isopropylalkohol Ltr CL-131

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

Isopropylalkohol Ltr CL-131

Other means of identification

Index No.: 603-117-00-0

EC No.: 200-661-7

CAS No.: 67-63-0

Unique formula identifier (UFI)

36QH-UUW6-7KD5-4ANN

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Cleaning product

Use descriptors (REACH)

Sectors of use	Description
LCS "PW"	Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
LCS "C"	Consumer uses: Private households (= general public = consumers)
Product category	Description
PC 35	Washing and Cleaning Products (including solvent based products)
Process category	Description
PROC 19	Hand-mixing with intimate contact and only PPE available
Environmental release category	Description
ERC 8a	Wide dispersive indoor use of processing aids in open systems

Uses advised against

None known.

1.3. Details of the supplier of the safety data sheet

Company and address

Pureno A/S

Gefionsvej 20

3400 Hillerød

Denmark

+45 70 260 267

Contact person

Lars Skaarup

E-mail

ls@pureno.dk

Revision

05/11/2025

SDS Version

4.0

Date of previous version

17/02/2025 (3.0)

1.4. Emergency telephone number

Contact the poison hotline: +45 82 12 12 12 (24 hour service)
See section 4 "First aid measures".

SECTION 2: Hazards identification

Classified according to Regulation (EC) No. 1272/2008 (CLP).

2.1. Classification of the substance or mixture

Flam. Liq. 2; H225, Highly flammable liquid and vapour.
Eye Irrit. 2; H319, Causes serious eye irritation.
STOT SE 3; H336, May cause drowsiness or dizziness.

2.2. Label elements

Hazard pictogram(s)



Signal word

Danger

Hazard statement(s)

Highly flammable liquid and vapour. (H225)
Causes serious eye irritation. (H319)
May cause drowsiness or dizziness. (H336)

Precautionary statement(s)

General

If medical advice is needed, have product container or label at hand. (P101)
Keep out of reach of children. (P102)

Prevention

Wash hands thoroughly after handling. (P264)
Wear eye protection/protective gloves/protective clothing. (P280)

Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing. (P305+P351+P338)
If eye irritation persists: Get medical advice/attention. (P337+P313)

Storage

Store in a well-ventilated place. Keep cool. (P403+P235)

Disposal

Dispose of contents/container in accordance with local regulation (P501)

Hazardous substances

propan-2-ol;isopropyl alcohol;isopropanol

Additional labelling

UFI: 36QH-UUW6-7KD5-4ANN

2.3. Other hazards

Additional warnings

The material contains peroxide forming substances, which can form hazardous levels of peroxides e.g. during distillation, evaporation or extraction.
This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.
This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2023/707.

SECTION 3: Composition/information on ingredients

3.1. Substances

Product/substance	Identifiers	% w/w	Classification	Note
-------------------	-------------	-------	----------------	------

propan-2-ol;isopropyl alcohol;isopropanol	CAS No.: 67-63-0 EC No.: 200-661-7 REACH: Index No.: 603-117-00-0	95-100%	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
---	--	---------	---

3.2. Mixtures

Not applicable. This product is a substance.

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

-

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

Upon irritation: rinse with water. In the event of continued irritation, seek medical assistance.

Eye contact

If in eyes: Flush eyes immediately with plenty of water or isotonic water (20-30 °C) for at least 5 minutes and continue until irritation stops. Remove contact lenses. Make sure to flush under upper and lower eyelids. If irritation continues, contact a doctor. Continue flushing during transport.

Ingestion

If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink.

In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

Burns

Rinse with water until pain stops then continue to rinse for 30 minutes.

4.2. Most important symptoms and effects, both acute and delayed

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

4.3. Indication of any immediate medical attention and special treatment needed

If eye irritation persists: Get medical advice/attention.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Highly flammable liquid and vapour.

In use may form flammable/explosive vapour-air mixture.

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO₂)

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact the chemical emergency services on 72 85 20 00 (24 h service) in order to obtain further advice.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.

Ensure adequate ventilation, especially in confined areas.

Avoid inhalation of vapours from spilled material.

Contaminated areas may be slippery.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.

Keep unauthorized persons away from the spill

6.3. Methods and material for containment and cleaning up

Limit spillage and collect using granular absorbent or similar materials, and dispose of it in accordance with the regulations on dangerous waste.

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Ground and bond container and receiving equipment.

Use explosion-proof [electrical/lighting/ventilating] equipment.

Use non-sparking tools.

Take action to prevent static discharges.

The product should be tested for peroxides before distillation or evaporation and tested for peroxide formation or discarded after 1 year.

Peroxide formation may be present anywhere in the container, including the sides, bottom, exterior and threaded cap.

Peroxide formation in ppm concentrations may not be visually observable and must be identified through the use of appropriate testing procedures. If any of the following conditions exist, the material may be explosively unstable and will require stabilization prior to use:

1. Material appears to be degraded and or contaminated.

2. Material appears to be discolored.

3. Deterioration or distortion of storage container.

4. Thermal shock (sunlight).

5. Age of material exceeds recommended storage time.

Avoid contact during pregnancy and while nursing.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers and store protected from moisture and light. Containers should be dated when opened and tested periodically for the presence of peroxides. Do not exceed storage time limits. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Take action to prevent static discharges.

Must be stored in a cool and well-ventilated area, away from possible sources of ignition.

Recommended storage material

Always store in containers of the same material as the original container.

Fire class

In accordance with the statutory order on flammable liquids the product is classified as a liquid of class I, subclass 1 (1 storage unit = 1 liter).

Storage conditions

> 0°C

< 50°C

Incompatible materials

Keep only in original packaging.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

propan-2-ol;isopropyl alcohol;isopropanol

Long term exposure limit (8 hours) (mg/m³): 490

Long term exposure limit (8 hours) (ppm): 200

Short term exposure limit (15 minutes) (mg/m³): 980

Short term exposure limit (15 minutes) (ppm): 400

Statutory order 1619 on exposure limits for substances and mixtures (19/12/2024)

DNEL

propan-2-ol;isopropyl alcohol;isopropanol

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	319mg/kg bw/dag
Long term – Systemic effects - General population	Dermal	319 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	888 mg/kg bw/dag
Long term – Systemic effects - Workers	Dermal	888 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	89mg/m ³
Long term – Systemic effects - General population	Inhalation	89 mg/m ³
Long term – Systemic effects - Workers	Inhalation	500 mg7m3
Long term – Systemic effects - Workers	Inhalation	500 mg/m ³
Short term – Systemic effects - General population	Inhalation	178 mg/m ³
Short term – Systemic effects - Workers	Inhalation	1000 mg/m ³
Long term – Systemic effects - General population	Oral	26mg/kg bw/dag
Long term – Systemic effects - General population	Oral	26 mg/kg bw/day
Short term – Systemic effects - General population	Oral	51 mg/kg bw/day

PNEC

propan-2-ol;isopropyl alcohol;isopropanol

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		140,9 mg/l
Freshwater		140.9 mg/L

Freshwater sediment	552 mg/kg
Freshwater sediment	552 mg/kg
Intermittent release	140,9 mg/l
Intermittent release (freshwater)	140.9 mg/L
Marine water	140,9 mg/l
Marine water	140.9 mg/L
Marine water sediment	552mg/kg
Marine water sediment	552 mg/kg
Predators	160 mg/kg
Sewage treatment plant	251 mg/l
Sewage treatment plant	2.251 g/L
Soil	28 mg/kg
Soil	28 mg/kg

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked.

Apply standard precautions during use of the product. Avoid inhalation of vapours.

Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Pay special attention to hands, forearms and face.

Measures to avoid environmental exposure

No specific requirements.

Individual protection measures, such as personal protective equipment

Generally

Use only CE marked protective equipment.

▼ Respiratory Equipment

Type	Class	Colour	Standards
Normally, personal respiratory equipment is not necessary			
A	Class 3 (High capacity)	Brown	EN14387



Skin protection

Recommended	Type/Category	Standards
Dedicated work clothing should be worn	-	-



Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards
Nitrile	0.3	> 60	EN374-2, EN374-3, EN388



Eye protection

Type	Standards
Safety glasses	EN166



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

Liquid

Colour

Colourless

▼ Odour / Odour threshold

No data available.

▼ pH

No data available.

Density (g/cm³)

0.79

▼ Kinematic viscosity

No data available.

Particle characteristics

Does not apply to liquids.

Phase changes

▼ Melting point/Freezing point (°C)

No data available.

Softening point/range (°C)

Does not apply to liquids.

Boiling point (°C)

82-83

Vapour pressure

6.02 Pa

▼ Relative vapour density

No data available.

▼ Decomposition temperature (°C)

No data available.

Data on fire and explosion hazards

Flash point (°C)

12

Flammability (°C)

The material is ignitable.

▼ Auto-ignition temperature (°C)

No data available.

▼ Lower and upper explosion limit (% v/v)

No data available.

Solubility

▼ Solubility in water

No data available.

▼ n-octanol/water coefficient (LogKow)

No data available.

▼ Solubility in fat (g/L)

No data available.

9.2. Other information

Other physical and chemical parameters

No data available.

▼ Oxidizing properties

No data available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Avoid static electricity.

Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure.

Risk of formation of explosive peroxides when distilled, evaporated or otherwise concentrated.

10.5. Incompatible materials

Keep only in original packaging.

10.6. ▼ Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

▼ Acute toxicity

Product/substance	propan-2-ol;isopropyl alcohol;isopropanol
Species:	Rabbit
Route of exposure:	Dermal
Test:	LD50
Result:	>2000 mg/kg ·

Product/substance	propan-2-ol;isopropyl alcohol;isopropanol
Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	5840 mg/kg ·

Product/substance	propan-2-ol;isopropyl alcohol;isopropanol
Species:	Rat
Route of exposure:	Inhalation
Test:	LC50
Result:	66,1mg/l 4 h ·

Product/substance	propan-2-ol;isopropyl alcohol;isopropanol
Species:	Rat
Route of exposure:	Inhalation
Test:	LC50
Result:	47,5mg/l 8 h ·

Based on available data for the mixture, the classification criteria are not met.

▼ **Skin corrosion/irritation**

Based on available data for the mixture, the classification criteria are not met.

Serious eye damage/irritation

Causes serious eye irritation.

▼ **Respiratory sensitisation**

Based on available data for the mixture, the classification criteria are not met.

▼ **Skin sensitisation**

Based on available data for the mixture, the classification criteria are not met.

▼ **Germ cell mutagenicity**

Based on available data for the mixture, the classification criteria are not met.

▼ **Carcinogenicity**

Based on available data for the mixture, the classification criteria are not met.

▼ **Reproductive toxicity**

Based on available data for the mixture, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness.

▼ **STOT-repeated exposure**

Based on available data for the mixture, the classification criteria are not met.

▼ **Aspiration hazard**

Based on available data for the mixture, the classification criteria are not met.

11.2. Information on other hazards

Long term effects

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs.

Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system.

Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

▼ **Endocrine disrupting properties**

This mixture/product does not contain any substances known to have hormone-disrupting properties in relation to health.

Other information

propan-2-ol;isopropyl alcohol;isopropanol has been classified by IARC as a group 3 carcinogen.

SECTION 12: Ecological information

12.1. ▼ Toxicity

Product/substance	propan-2-ol;isopropyl alcohol;isopropanol
Species:	Algae
Duration:	8 days
Test:	NOEC
Result:	>1800 mg/l ·

Product/substance	propan-2-ol;isopropyl alcohol;isopropanol
Species:	Fish
Duration:	96 hours
Test:	LC50
Result:	8970-9280 mg/l ·

Product/substance	propan-2-ol;isopropyl alcohol;isopropanol
Species:	Daphnia
Duration:	24 hours
Test:	EC50
Result:	9714 mg/l ·

Product/substance	propan-2-ol;isopropyl alcohol;isopropanol
Species:	Crustacean
Duration:	18 hours
Test:	EC10
Result:	5175 mg/l ·

Product/substance	propan-2-ol;isopropyl alcohol;isopropanol
Species:	Crustacean
Duration:	No data available.
Test:	EC50
Result:	>1000mg/l ·

Based on available data for the mixture, the classification criteria are not met.

12.2. Persistence and degradability

Product/substance	propan-2-ol;isopropyl alcohol;isopropanol
Result:	95%
Conclusion:	Readily biodegradable
Test:	OECD 301 E

12.3. Bioaccumulative potential

Product/substance	propan-2-ol;isopropyl alcohol;isopropanol
Conclusion:	No potential for bioaccumulation

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

12.6. ▼ Endocrine disrupting properties

This mixture/product does not contain any substances considered to have endocrine-disrupting properties in relation to the environment.

12.7. Other adverse effects

None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product is covered by the regulations on hazardous waste. (*)

To the extent the material has not been subject to regular tests of peroxide formation the waste shall be treated as explosive waste.

HP 3 - Flammable

HP 4 - Irritant (skin irritation and eye damage)

Dispose of contents/container to an approved waste disposal plant.

Commission Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

EWC code

20 01 13* Solvents

Waste group

Gr. C Waste with high energy content

Specific labelling

Not applicable.

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other informatio n:
ADR	UN1219	ISOPROPANOL (ISOPROPYL ALCOHOL)	Transport hazard class: 3 Label: 3 Classification code: F1 	II	No	Limited quantities: 1 L Tunnel restriction code: (D/E) See below for additional information.
IMDG	UN1219	ISOPROPANOL (ISOPROPYL ALCOHOL)	Transport hazard class: 3 Label: 3 Classification code: F1 	II	No	Limited quantities: 1 L EmS: F-E S-D See below for additional information.
IATA	UN1219	ISOPROPANOL (ISOPROPYL ALCOHOL)	Transport hazard class: 3 Label: 3 Classification code: F1 	II	No	See below for additional information.

* Packing group

** Environmental hazards

Additional information

This product is within scope of the regulations of transport of dangerous goods.

ADR / See Table A, section 3.2.1 for any information on special provisions, requirements, or warnings in connection with transport. See section 5.4.3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.

IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.

IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.

14.6. Special precautions for user

Not applicable.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

People under the age of 18 shall not be exposed to this product.

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

Demands for specific education

No specific requirements.

SEVESO - Categories / dangerous substances

P5c - FLAMMABLE LIQUIDS, Qualifying quantity (lower-tier): 5.000 tonnes / (upper-tier): 50.000 tonnes

REACH, Annex XVII

propan-2-ol;isopropyl alcohol;isopropanol is subject to REACH restrictions (entry 40).

Additional information

Tactile warning.

Sources

The Danish Working Environment Authority's executive order no. 1049 of 30 May 2021 on young people's work. Based on Council Directive 94/33 / EC of 22 June 1994 on the protection of young people at work. Pregnant workers and workers who are breastfeeding (AT Guide A.1.8-6, amended 2024). Executive Order no. 372 of 25 April 2016 on control of the risk of major accidents with dangerous substances. Commission Regulation (EU) No 1357/2014 of 18 December 2014 on waste. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (CLP). Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

15.2. Chemical safety assessment

No

SECTION 16: Other information**Full text of H-phrases as mentioned in section 3**

H225, Highly flammable liquid and vapour.

H319, Causes serious eye irritation.

H336, May cause drowsiness or dizziness.

The full text of identified uses as mentioned in section 1

LCS "PW" = Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

LCS "C" = Consumer uses: Private households (= general public = consumers)

PROC 19 = Hand-mixing with intimate contact and only PPE available

PC 35 = Washing and Cleaning Products (including solvent based products)

ERC 8a = Wide dispersive indoor use of processing aids in open systems

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CE = Conformité Européenne (European conformity)

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial chemical Substances

ES = Exposure Scenario

EUH statement = CLP-specific Hazard statement

EuPCS = European Product Categorisation System

EWC = European Waste Catalogue

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

GWP = Global warming potential

IARC = International Agency for Research on Cancer (IARC)

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

OECD = Organisation for Economic Co-operation and Development

PBT = Persistent, Bioaccumulative and Toxic

PNEC = Predicted No Effect Concentration

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RRN = REACH Registration Number

SCL = A specific concentration limit

SVHC = Substances of Very High Concern

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TWA = Time weighted average

UN = United Nations

UVBC = Unknown or variable composition, complex reaction products or of biological materials

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the mixture in regard of health hazards is in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP).

The classification of the mixture in regard to physical hazards has been based on experimental data.

The safety data sheet is validated by

Lisbet Tetsche

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: DK-en